

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## GENERAL EMERGENCY ALARM SYSTEM

# YLX120-24Z Marine Electric Bell

Description: Marine electric bell is an important and simple communication and alarm tool on board, which can send out special signals in time to indicate the occurrence of some abnormal phenomena. It is also a com...

ISO9001 Supplier

Class Certificate

Export Supply



### Key Highlights

|               |  |
|---------------|--|
| Category      | General Emergency Alarm System             |
| Standard      | EN   |
| Weight / Size | Working voltage DC24V 7.Net weight:        |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

|             |  |               |                                      |
|-------------|--|---------------|--------------------------------------|
| Category    | General Emergency Alarm System             | Model / SKU   | YLX120-24Z-Marine-Electric-Bell      |
| Standard    | EN   | Weight / Size | Working voltage DC24V 7.Net weight:  |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty      | 12 Months unless specified otherwise |
| Origin      | China                                      |               |                                      |

#### CONTENTS

 Description:

 Technical data:

## Description:

Marine electric bell is an important and simple communication and alarm tool on board, which can send out special signals in time to indicate the occurrence of some abnormal phenomena. It is also a companion instrument to the ship's telephones, communications equipment, telegraph bells and other electrical equipment.



## Technical data:

1. applicable ambient temperature :-25°C~+55°C;
2. the power supply voltage in the rated DC±15%, AC +6%~-10% of the range of change,
3. can work reliably, the sound intensity is not less than the specified value;
4. Protection level :IP56;
5. Outer diameter of cable :φ14-φ16.
6. Working voltage DC24V
7. Net weight: 2.1kg