

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

YACHT WINDLASS & WINCH

Yatch Vertical Windlass With AC Mode

Yatch Vertical Windlass With AC Mode AC Vertical windlass (3000W,4000W,5500W,7500W)
Stainless steel vertical windlass. Available in high or low profile, with different drives and for boats up to 50m. The NYS ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

| | |
|---------------|---|
| Category | Yacht Windlass & Winch |
| Standard | DIN |
| Material | Stainless steel 304,316, 316L |
| Weight / Size | lift load 2500KG 3100KG 3500KG 3600KG Working load 1400KG 1600KG 1700KG ... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

| | | | |
|---------------|--|-------------|--|
| Category | Yacht Windlass & Winch | Model / SKU | Yatch-Vertical-Windlass-With-AC-Mode |
| Standard | DIN | Material | Stainless steel 304,316, 316L |
| Weight / Size | lift load 2500KG 3100KG 3500KG 3600KG Working load 1400KG 1600KG 1700KG 1800KG Line speed 15m/min 15m/min 15m/min 15m/min Chain(DIN766) 12.5mm-13mm 14mm 16mm 18mm | Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS |
| Warranty | 12 Months unless specified otherwise | Origin | China |

CONTENTS

- Yatch Vertical Windlass With AC Mode
- AC Vertical windlass (3000W,4000W,5500W,7500W)
- Main parameter

Yatch Vertical Windlass With AC Mode

AC Vertical windlass (3000W,4000W,5500W,7500W)

Stainless steel vertical windlass. Available in high or low profile, with different drives and for boats up to 50m. The NYS windlass can use chains up to 18mm with stud link in diameter. Possibility of 230V,400V ,12V,24V

Main parameter

| AC Specification | | | | |
|------------------|-------------|-----------|-----------|-----------|
| Electric motor | 3000W | 4000W | 5500W | 7500W |
| Motor supply | 12V/24V | 230V/400V | 230V/400V | 230V/400V |
| Max. lift load | 2500KG | 3100KG | 3500KG | 3600KG |
| Working load | 1400KG | 1600KG | 1700KG | 1800KG |
| Line speed | 15m/min | 15m/min | 15m/min | 15m/min |
| Chain(DIN766) | 12.5mm-13mm | 14mm | 16mm | 18mm |