

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

YACHT WINDLASS & WINCH

Yatch Vertical Windlass with DC Model

Yatch Vertical Windlass with DC Model Features 1.Vertical design suits powerboats or sailboats and can be utilized for anchor ropes, as docking capstans on larger craft, or auxiliary line hauling. 2.Hig...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Yacht Windlass & Winch
Standard	EN
Material	Stainless steel 304,316, 316L
Weight / Size	Main Parameter Specifications Model Weight Power Motor No load Max Max.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Yacht Windlass & Winch	Model / SKU	Yatch-Vertical-Windlass-with-DC-Model
Standard	EN	Material	Stainless steel 304,316, 316L
Weight / Size	Main Parameter Specifications Model Weight Power Motor No load Max Max.	Surface	2.High-quality polished 316 stainless steel surface makes for a good appearance.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Yatch Vertical Windlass with DC Model
- Features
- Main Parameter

Yatch Vertical Windlass with DC Model

Features

- 1.Vertical design suits powerboats or sailboats and can be utilized for anchor ropes, as docking capstans on larger craft, or auxiliary line hauling.
- 2.High-quality polished 316 stainless steel surface makes for a good appearance.
- 3.Simplified installation by modular design and precise alignment of gearbox to the top works utilizing marine-grade stainless steel studs.
- 4.Rope-chain gypsy, choice of two gypsy.
- 5.Fit include hand-switch, foot-switch, control box and wrench.

Main Parameter

Specifications									
Model	Weight	Power	Motor	No load	Max	Max.	Line	Rope	Chain
net(kg)	(W)	absorption	Load	Pull	Speed	Size	Size		
YD411	12	12V/24V	400	30A	125KG	420KG	30m/min	12-14mm	6-7mm
YD411H	12.6	12V/24V	400	30A	130KG	450KG	30m/min	12-14mm	6-7mm
YD511	12.3	12V/24V	600	60A	186KG	560KG	25m/min	12-14mm	6-7mm
YD511H	13	12V/24V	600	60A	210KG	600KG	25m/min	12-14mm	6-7mm
YD611	19	12V/24V	800	100A	250KG	700KG	20m/min	16-20mm	8-10mm
YD611H	21	12V/24V	800	100A	280KG	700KG	20m/min	16-20mm	8-11mm
YD711	24	12V/24V	1200	120A	400KG	1200KG	20m/min	16-20mm	8-12mm
YD711H	25.5	12V/24V	1200	120A	400KG	1200KG	20m/min	16-20mm	8-13mm
YD811	26	12V/24V	1600	140A	560KG	1600KG	20m/min	16-20mm	8-14mm
YD811H	27.5	12V/24V	1600	140A	560KG	1600KG	20m/min	16-20mm	8-15mm
YD811	29	12V/24V	2000	170A	660KG	1900KG	20m/min	20-24mm	10-12.5mm
YD811H	31.5	12V/24V	2000	170A	660KG	1900KG	20m/min	20-24mm	10-12.5mm
YD1011	25	12V/24V	1600	140A	560KG	1600KG	20m/min	20-24mm	10-12.6mm
YD1011H	27.5	12V/24V	1600	140A	560KG	1600KG	20m/min	20-24mm	10-12.7mm
YD1011	30.5	12V/24V	2000	170A	660KG	1900KG	20m/min	20-24mm	10-12.8mm
YD1011H	33	12V/24V	2000	170A	660KG	1900KG	20m/min	20-24mm	10-12.9mm