

# Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

ELECTRIC HEATER


## ZX-5DCZ Marine Electromagnetic Range

ISO9001 Supplier

Class Certificate

Export Supply

Marine Electromagnetic Range Product introduction: 1. The shell adopts 304 stainless steel material, durable; 2. The core component (microcrystalline panel, core) imported from Germany, the greatest deg...

	Key Highlights	
	Category	Electric Heater
	Standard	EN
	Material	Stainless steel 304
	Weight / Size	Model Dimension(mm) Capacity(people) Power (kw) Volts(v) HZ N/W(kg) ZX-3...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	
<p>We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.</p>		

Technical Specifications			
Category	Electric Heater	Model / SKU	ZX-5DCZ-Marine-Electromagnetic-Range
Standard	EN	Material	Stainless steel 304
Weight / Size	Model Dimension(mm) Capacity(people) Power (kw) Volts(v) HZ N/W(kg) ZX-3DCZ 420X550X390 10 3 380v/415v/440v/480v-3p 50/60Hz 20 ZX-5DCZ 700X700X850 20 5 380v/415v/440v/480v-3p 50/60Hz 60 ZX-8DCZ 800X800X850 30 8 380v/415v/440v/480v-3p 50/60Hz 75 ZX-10DCZ 1200X800X850 50 2x5 380v/415v/440v/480v-3p 50/60Hz 90 ZX-16DCZ 1200X800X850 60 2x8 380v/415v/440v/480v-3p 50/60Hz 105	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ Marine Electromagnetic Range	■ Product introduction:
	■ Technical data:	

## Marine Electromagnetic Range

### Product introduction:

1. The shell adopts 304 stainless steel material, durable;
2. The core component (microcrystalline panel, core) imported from Germany, the greatest degree of protection of stable and reliable performance;
3. The easy to use, fast heating speed, no fire, smoke-free, no emissions, good safety;
4. The fifth is provided with a power regulation switch and digital display;
5. The adjustable foot, adjustable range of positive and negative 30mm.

### Technical data:

Model	Dimension(mm)	Capacity(people)	Power (kw)	Volts(v)	HZ	NW(kg)
ZX-3DCZ	420X550X390	10	3	380v/415v/440v/480v-3p	50/60Hz	20
ZX-5DCZ	700X700X850	20	5	380v/415v/440v/480v-3p	50/60Hz	60
ZX-8DCZ	800X800X850	30	8	380v/415v/440v/480v-3p	50/60Hz	0.061524s

ZX-10DCZ	1200X800X850	50	2x5	380v/415v/440v/480v-3p	50/60Hz	90
ZX-16DCZ	1200X800X850	60	2x8	380v/415v/440v/480v-3p	50/60Hz	105