

**ELECTRIC HEATER**


# ZX-D1200 Electric 6 Hot-Plate Cooker With Oven

ISO9001 Supplier

Class Certificate

Export Supply

Electric 6 Hot-Plate Cooker With Oven Product introduction : 1. The shell adopts 304 stainless steel material, thickness of up to 1.5mm, to ensure sufficient strength of the table. 2. The core components...



Key Highlights

<b>Category</b>	Electric Heater
<b>Standard</b>	EN
<b>Material</b>	SUS304, SUS316L
<b>Weight / Size</b>	Model Dimension(mm) Power (kw) Volts(v) HZ N/W(kg) ZX-D1200 1200X900X850...
<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
<b>Category</b>	Electric Heater	<b>Model / SKU</b>	ZX-D1200-Electric-6-Hot-Plate-Cooker-With-Oven
<b>Standard</b>	EN	<b>Material</b>	SUS304, SUS316L
<b>Weight / Size</b>	Model Dimension(mm) Power (kw) Volts(v) HZ N/W(kg) ZX-D1200 1200X900X850 6x4 kw 380v/415v/440v/480v-3p 50/60Hz 120 ZX-D1200K 1200X900X850 6x4 kw+4.8kw 380v/415v/440v/480v-3p 50/60Hz 180 ZX-D1050 1050X700X850 6x2.6 kw 380v/415v/440v/480v-3p 50/60Hz 100 ZX-D1050K 1050X700X850 6x2.6 kw+4.8kw 380v/415v/440v/480v-3p 50/60Hz 150	<b>Certificate</b>	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
<b>Warranty</b>	12 Months unless specified otherwise	<b>Origin</b>	China

<b>CONTENTS</b>	<ul style="list-style-type: none"> <li>■ Electric 6 Hot-Plate Cooker With Oven</li> <li>■ Technical data:</li> </ul>	<ul style="list-style-type: none"> <li>■ Product introduction :</li> </ul>
-----------------	--	--

## Electric 6 Hot-Plate Cooker With Oven

### Product introduction :

1. The shell adopts 304 stainless steel material, thickness of up to 1.5mm, to ensure sufficient strength of the table.
2. The core components (such as electric heating plate, temperature controller etc.) imported from Germany, the greatest degree of protection of stable and reliable performance.
3. The six files can adjust the electric cooker, electric heating plate each separate control knob.
4. The oven temperature control range from 60 to 340°C adjustable.
5. The over temperature protection function, the highest temperature limit of 340°C to ensure safe use.
6. The adjustable foot, adjustable range of positive and negative 30mm.

## Technical data:



Model	Dimension(mm)	Power (kw)	Volts(v)	HZ	N/W(kg)
ZX-D1200	1200X900X850	6x4 kw	380v/415v/440v/480v-3p	50/60Hz	120
ZX-D1200K	1200X900X850	6x4 kw+4.8kw	380v/415v/440v/480v-3p	50/60Hz	180
ZX-D1050	1050X700X850	6x2.6 kw	380v/415v/440v/480v-3p	50/60Hz	100
ZX-D1050K	1050X700X850	6x2.6 kw+4.8kw	380v/415v/440v/480v-3p	50/60Hz	150