

Jinbo Marine

Marine & Offshore Equipment Datasheet

PRODUCT DATASHEET

MARINE COMMUNICATION EQUIPMENT

ZXF-N2000 Ex-Pro VHF

FEATURES: Use on-board tankers or for fire service communication. Designed to comply with IMO MSC338 (91) and IMO MSC. 149 (77). Includes 19 VHF simplex channels assigned to marine use by ITU. Private channels or ot...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Communication Equipment
Weight / Size	Small, lightweight and easy-to-use.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Communication Equipment	Model / SKU	ZXF-N2000-Ex-Pro-VHF
Weight / Size	Small, lightweight and easy-to-use.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

■ FEATURES:

■ Specification:

FEATURES:

Use on-board tankers or for fire service communication.

Designed to comply with IMO MSC338 (91) and IMO MSC. 149 (77).

Includes 19 VHF simplex channels assigned to marine use by ITU. Private channels or other channel are optional.

Small, lightweight and easy-to-use.

Watertight to a depth of 1 m for at least 5 min and not unduly affected by seawater or oil.

External PTT & Skull Mic/Headset can be attached as optional.

EX-PRO design. CQST EX-PRO approval (Cer. No.: CNEx15.0497).

Speification:

Frequency & Channel	
Frequency range:	156.300 ~ 156.875MHz
Channel Space:	25kHz
Usable Channels:	19 channels (default)
Technical Features	
Output Power:	HIGH 3.0W / LOW 0.5W
Communication Methods:	Simplex
Warming Up Time:	Within 5 Sec
Squelch Control:	/
Dual Watch:	/
Key Locking:	/
Battery Save Mode:	/
Beep Establishment:	/
Location Indication:	/
Operating Temperature:	-20°C~ + 60°C
Dimension:	256 (H) X 51 (W) X 33 (D) mm
Weight:	280g (Transceiver+Battery)
IP Grade:	IP66 (Transceiver/Battery) IP22 (Charger/Adaptor)
Ex code:	Exib IIB T3 Gb
Rechargeable Battery	
Battery Capacity:	2200mAh
Battery Voltage:	7.2V (DC)