

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## OIL PURIFIER

## ZYC Series Multi Function High Efficient Vacuum Oil Purifier

ISO9001 Supplier

Class Certificate

Export Supply

Description: The product can be used for above 110KV transformer installation and overhaul, as well as for treatment to non-conformable transformer oil, mutual inductor oil and circuit breaker oil in power indu...




### Key Highlights

Category	Oil Purifier
Standard	EN
Material	Unique water and gas removing material, offer 700 times the evaporation ...
Weight / Size	Unique water and gas removing material, offer 700 times the evaporation ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Oil Purifier	Model / SKU	ZYC-Series-Multi-Function-High-Efficient-Vacuum-Oil-Purifier
Standard	EN	Material	Unique water and gas removing material, offer 700 times the evaporation area size of the common one.
Weight / Size	Unique water and gas removing material, offer 700 times the evaporation area size of the common one.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China



**CONTENTS**

- China ZYC Series Multi Function High Efficient Vacuum Oil Purifier:
- Description:
- Technical Data:

## China ZYC Series Multi Function High Efficient Vacuum Oil Purifier:

### Description:

The product can be used for above 110KV transformer installation and overhaul, as well as for treatment to non-conformable transformer oil, mutual inductor oil and circuit breaker oil in power inductor (especially applicable to recovery of extremely inferior insulation oil, as well as for transformer vacuum oil filling and drying.

#### Technical Feature:

The machine is double-stage vacuum system, it could fast to remove the water, gas and impurities, but also could regenerate the extremely inferior insulation oil. It could sufficiently remove the intensive oxide and free carbon, thus resumes anti-oxidation, medium consumption, acid/alkali water solubility characteristics. After the treatment, the oil can meet the national standard in respect of water content, withstand value, gas content, acid value and medium consumption requirement.

After the treatment, the breakdown voltage could enhance to 75KV or above .


Unique water and gas removing material, offer 700 times the evaporation area size of the common one.

The latest decolorant is selected which ensure dark color oil to resume the color of the new oil.

Ultra high precision filter, the filtration size could be  $\leq 1\mu\text{m}$ .

### Technical Data:

Item	Unit	ZYC-50	ZYC-100	ZYC-150	ZYC-200	ZYC-250	ZYC-300
Flow Rate	L/min	50	100	150	200	250	300
working vacuum	pa	$\leq 133$					
Ultimate vacuum	pa	$\leq 5$					
working Preusre	Mpa	$\leq 0.4$					
Constant temperature control range	$^{\circ}\text{C}$	20 ~ 80					
power	/	380V/50HZ(at user's option)					
noise db(A)	dB(A)	$\leq 65 \sim 80$ ( depend on user's requirement )					
Fult-free working hours	h	$\geq 4000$					
continuous hours	h	$\geq 150$					
Heating power	Kw	30	72	96	144	168	192
Total Power	Kw	35	78	106	155	185	210
Inlet(outlet) diameter	mm	$\Phi 32$	$\Phi 42$	$\Phi 50$	$\Phi 50$	$\Phi 60$	$\Phi 60$
weight	kg	650	1050	1350	1450	2000	2500



After filtration	breakdown voltage	KV	$\geq 75$
	water content	ppm	$\leq 3$
	Dielectric loss	$\text{tg}\delta ( 90^{\circ}\text{C} ) \%$	$\leq 0.3$
	acid value	mgKOH/g	$\leq 0.03$
	gas content	%	$\leq 0.1$
	granularity	$\mu\text{m}$	$\leq 1$ ( at user's option )