MARINE OIL WATER SEPERATOR

ZYFM-B Series Marine Bilge Separator

ZYFM-B series marine bilge separator is widely used for ship bilge water,port oily water treatment,the device is consist of 1st and 2nd grade separator,special purpose pump,electric control box,oil concentration alarm...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Oil Water Seperator
Standard	DIN
Weight / Size	1 2 Power supply 220V 50HZ,380V 50HZ, 410V 50HZ,440V 60HZ Gathering room...
Certificate	CCS,BV, ABS, GL, DNV certificate etc.

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Oil Water Seperator	**Model / SKU**	ZYFM-B-Series-Marine-Bilge-Separator
Standard	DIN	**Weight / Size**	1 2 Power supply 220V 50HZ,380V 50HZ, 410V 50HZ,440V 60HZ Gathering room heating method and power Electric heating 1kw 1kw 2kw 2kw 2kw 3kw Oil drainage mode Automatic and manual Dimension(LXWXH) 1590X950X1350 1600X1080X1860 1800X1100X1910 2170X1310X2160 2250X1380X2250 2560X1600X2400 Weight(kg) 300 500 700 1200 1600 2200
Certificate	CCS,BV, ABS, GL, DNV certificate etc.	**Warranty**	12 Months unless specified otherwise
Origin	China		

China ZYFM-B Series Marine Bilge Separator:

ZYFM-B series marine bilge separator is widely used for ship bilge water,port oily water treatment,the device is consist of 1st and 2nd grade separator,special purpose pump,electric control box,oil concentration alarm recording instrument, etc. It features lighter,smaller,convenient and long service life.

Model Number	ZYFM-0.25	ZYFM-0.5	ZYFM-1	ZYFM-2	ZYFM-3	ZYFM-5
Treatment capability (m3 per hour)	0.25	0.5	1	2	3	5
Discharging standard	Equal or less than 15ppm					
Design pressure	0.2 Mpa					
Types of pump	Single screw pump / plunger pump					
Suction lift(m)	Equal or less than 6					
Power of motor(kw)	0.75	1.1	1.5	1.5	2.2	2.2
Electric heating power	..	1		2		
Power supply	220V 50HZ,380V 50HZ, 410V 50HZ,440V 60HZ					

Gathering room heating method and power	Electric heating					
	1kw	1kw	2kw	2kw	2kw	3kw
Oil drainage mode	Automatic and manual					
Dimension(LXWXH)	1590X950X1350	1600X1080X1860	1800X1100X1910	2170X1310X2160	2250X1380X2250	2560X1600X2400
Weight(kg)	300	500	700	1200	1600	2200