

MARINE DAVIT AND CRANE

A davit

A davit Main parameters SWL 12.5 t Hoisting speed ≥18m /min Lowering speed 0-30m /min Drum capacity 30 m Luffing speed 60sec Size of wire:4Vx39+5FC-1770-32- zinc.(anti-rotary),M.B.L=777kN Heel/Trim 200/100...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Davit and crane
Standard	DIN
Material	Cast steel
Weight / Size	A davit Main parameters SWL 12.5 t Hoisting speed ≥18m /min Lowering spe...
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS, MED

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Davit and crane	Model / SKU	A-davit
Standard	DIN	Material	Cast steel
Weight / Size	A davit Main parameters SWL 12.5 t Hoisting speed ≥18m /min Lowering speed 0-30m /min Drum capacity 30 m Luffing speed 60sec Size of wire:4Vx39+5FC-1770-32-zinc.(anti-rotary),M.B.L=777kN Heel/Trim 200/100 Main power supply 440 V/ 60 Hz/ 3 Phase Power of pump station 75 kw Ambient temperature -200-45 Brief Construction This launching appliance consists of lifting arm, hoisting mechanism, hydraulic swing mechanism, remote control unit, limit unit, accumulator, and hydraulic system etc.	Certificate	ABS,LR, BV, GL, CCS, RINA, IRS, MED
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	A davit Brief Construction
----------	--

A davit

Main parameters

SWL 12.5 t

Hoisting speed ≥18m /min

Lowering speed 0-30m /min

Drum capacity 30 m

Luffing speed 60sec

Size of wire:4Vx39+5FC-1770-32- zinc.(anti-rotary),M.B.L=777kN

Heel/Trim 200/100

Main power supply 440 V/ 60 Hz/ 3 Phase

Power of pump station 75 kw

Ambient temperature -200-45

Brief Construction

This launching appliance consists of lifting arm, hoisting mechanism, hydraulic swing mechanism, remote control unit, limit unit, accumulator, and hydraulic system etc.

The lifting arm is a mainly holding structure of the launching appliance. It can accomplish turning the work boat and rescue boat from inboard to outboard position depending on the outriggered arm.

The hoisting mechanism is a main assembly for recovering and launching work boat /rescue boat. It controls lowering and hoisting of wire of hoisting mechanism through head block so as to achieve the aim of recovering and launching work boat /rescue boat.

The limit devices are a security device for avoiding the work boat /rescue boat from overloading and hydraulic system from over-pressure.

The remote control unit is used for effectively controlling the lowering height of work boat /rescue boat through the remote control wires operated from a position within the work boat /rescue boat in case that all passengers have embarked boat and there is no any operator on the deck.

The cylinder is designed for safe buffering in extreme positions.

Hydraulic circuit has a full flow return filter with changeable filter core inserts.

Hydraulic power piping will be supplied in stainless steel SUS304.

The cylinder is designed for marine use and has spherical bearings on axles. The piston rod is chrome plated to prevent rust attack.

The launching appliance is designed with manual pump for emergency lowering of load in case of power failure.

Available for CCS, RINA, MED, LR, DNV, BV certificate