

MANUAL OPERATED FIRE MONITOR

Adjustable Foam And Water Fire Monitor PS24-64B

ISO9001 Supplier

Class Certificate

Export Supply

Type: PL24-64B Flow Range: 24-64 L/S Adjustable (380-1000GPM) Working Pressure: 10 bar Max Reach @ Max Flow: 65m (Water) and 60M (Foam) Range of motion: -45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : A...



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Mat...
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Mat...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	Model / SKU	Adjustable-Foam-And-Water-Fire-Monitor-PS24-64B
Standard	EN	Material	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Material (Gear) : bronze Material (nozzle) : Aluminum, with stream sharper Material (handwheel) : chromate cast iron Pump requirement for minimum performance : 64L/S@ 8 bar Pipe dimensions for installation:
Weight / Size	-45°~+90°Vert , 360°Rot Max fog angle : 120° Material (body) : Aluminum Material (Gear) : bronze Material (nozzle) : Aluminum, with stream sharper Material (handwheel) : chromate cast iron Pump requirement for minimum performance : 64L/S@ 8 bar Pipe dimensions for installation:	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Adjustable Foam And Water Fire Monitor PS24-64B:

Type: PL24-64B

Flow Range: 24-64 L/S Adjustable (380-1000GPM)

Working Pressure: 10 bar

Max Reach @ Max Flow: 65m (Water) and 60M (Foam)

Range of motion: -45°~+90°Vert , 360°Rot

Max fog angle : 120°

Material (body) : Aluminum

Material (Gear) : bronze

Material (nozzle) : Aluminum, with stream sharper

Material (handwheel) : chromate cast iron

Pump requirement for minimum performance : 64L/S@ 8 bar

Pipe dimensions for installation: 4 Inch

Monitor Inlet: DN100 flange

Monitor Outlet : 2.5 inch (65mm)

Paint: Fire Red