

MARINE ELECTRICAL INSTRUMENT

Alternating Current Network Insulation Electrical Resistance Monitor

- ISO9001 Supplier
- Class Certificate
- Export Supply

Alternating Current Network Insulation Electrical Resistance Monitor Model number:Q96-ZMΩ F96-MΩ AH96-MΩ 51L5-MΩ (without alarm signal output insulation meter,Wide angle 240 degree) Model number:Q96-MΩ F96-M...



Key Highlights	
Category	Marine Electrical Instrument
Standard	DIN
Material	Direction of mounting Vertical Front size of instrument Q/F96(96X96)mm,Q...
Weight / Size	The deflection angle of 51C4,51L4,51T4,51C6,51T6 Pointer needle is right...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications			
Category	Marine Electrical Instrument	Model / SKU	Alternating-Current-Network-Insulation-Electrical-Resistance-Monitor
Standard	DIN	Material	Direction of mounting Vertical Front size of instrument Q/F96(96X96)mm,Q/F72(72X72)mm New 45 type (110X110)mm,New 63 type (80X80)mm Meter overshoot When the pointer needle reach 2/3 of ful scale,less than 20% Insulation,Voltage-endurance electric circuit and shell AC:2600V / 1 minute(water area) Vibration resistance 24.5m/S2 Shock resistance 147m/S2 Meter material square type:
Weight / Size	The deflection angle of 51C4,51L4,51T4,51C6,51T6 Pointer needle is right angle(90 degree),also can be extend to wide angle(240 degree) deflection angle.(need to confirm when you place order) (96x96mm) Q/F 96 type wide angle meter,overall size 96x96mm, hole size 92x92mm,depth dimensions 108mm.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Alternating Current Network Insulation Electrical Resistance Monitor:	■ Application Of Our Marine Meter:
	■ Product Description:	■ Universal Technical Parameter:

China Alternating Current Network Insulation Electrical Resistance Monitor:

Alternating Current Network Insulation Electrical Resistance Monitor

Model number:Q96-ZMΩ F96-MΩ AH96-MΩ 51L5-MΩ (without alarm signal output insulation meter,Wide angle 240 degree)

Model number:Q96-MΩ F96-MΩ AH96-MΩ (without alarm signal output insulation meter,Right angle 90 degree)

Model number:Q96-ZMΩA F96-BMΩ AH96-BMΩ 51L5-BMΩ (with alarm signal output insulation meter,Wide angle 240 degree)

Model number:F96-BMΩ Q96-MΩA AH96-BMΩ (with alarm signal output insulation meter,Right angle 90degree)

Model number:F96D-BMΩ Q96D-MΩA AH96D-BMΩ (Double circuit alternating Current Network Insulation Electrical Resistance Monitor,double structure)

Q/F 96-BMΩ Alternating Current Network Insulation Electrical Resistance Monitor can be used to monitoring the non ground connection type alternating power distribution system which is below 500V continuously,and it will produce soundlight alarm signal when the electrical circuit insulation electrical resistor when exception occurs,insulation electrical resistance lower than the alarm value of instrument.

The meter can be work normally after charging it 5 minutes later,effective range is 0.05-5Ω.

The effective meter measure range is 0.005-5Ω,alarm value class have 10KΩ,30KΩ,60KΩ,100KΩ,total four class. or alarm value 0.1KΩ,0.2KΩ,0.3KΩ,0.5KΩ,

Application Of Our Marine Meter:

Its structure is magnetic electric tension string supporting and pivot needle type structure.

Rotating part no friction,work reliable,high mechanical shock resistance.Vibration will be proceed under the condition of acceleration 0.7g. Due to the mobile part of ivot needle adopt spring bearing support which can reduce the shock and vibration, pivot needle and bearing consists of high hardness cobalt-tungsten and barklyite,vibration can be proceed under the condition of acceleration 0.7g.

Advanced converter line and Indicating device integration structure,the instrument is high accuracy and large angle.The meter have linear scale,and won't affect by the magnetic filed outside,all adopt printed dial,colorized dial,scale is very clear,look neat and beautiful.Null meter reading instrument all have zero button,easy to adjust.

Type:Alternating current (AC), Direct current(DC).

Product Description:

The deflection angle of Q96,F96,F96J,51L5,51T5,51C5,Z96,LS-96 Pointer needle is wide angle(240 to 250 degree),the meter is tension string structure,import of German technology,rotation no friction,shock assistance is better. Hairspring structure import of Taiwan technology,shock assistance is good,also can be produce to right angle 90 degree deflection angle.

The deflection angle of 51C4,51L4,51T4,51C6,51T6 Pointer needle is right angle(90 degree),also can be extend to wide angle(240 degree) deflection angle.(need to confirm when you place order) (96x96mm)

Q/F 96 type wide angle meter,overall size 96x96mm, hole size 92x92mm,depth dimensions 108mm.

Q/F 96 type right angle meter,overall size 96x96mm, hole size 92x92mm,depth dimensions 108mm.

Universal Technical Parameter:

Item	Technical performance	Equivalent international standard
Product technical standard:	GB/T7676-1998	IEC60092-504
Service environment standard:	GB8355-1987	IEC92-504-74
Product safety standard:	GB4793-2001	IEC61010

Accuracy grade	Frequency 0.5 grade, Power factor meter 3.0 grade, other 1.5 grade
Service temperature	-10~55°C,13°C~33°Cconform to accuracy grade 100%
Rotation angle of needle	Wide angle(250 degree) , Right angle(90 degree), Synchronous dial indicator
Protection grade	Shell protection conform to IP42,allow the exist of oil mist,salt mist,dust etc.
Color of watchcase	Square type white color, Round square black color ,panel border,terminal block,black.
Dial color	Convention color white, black need to customized.
Direction of mounting	Vertical
Front size of instrument	Q/F96(96X96)mm,Q/F72(72X72)mm
	New 45 type (110X110)mm,New 63 type (80X80)mm
Meter overshoot	When the pointer needle reach 2/3 of ful scale,less than 20%
Insulation,Voltage-endurance	electric circuit and shell AC:2600V / 1 minute(water area)
Vibration resistance	24.5m/S2
Shock resistance	147m/S2
Meter material	square type: watchcase/terminal block(flame retardant ABS), Watch cap(transparent glass) Round square shape:water cap(transparent PC)