

MANUAL OPERATED FIRE MONITOR

Aluminum Manual Fire Monitor PS80-HM-CN

ISO9001 Supplier

Class Certificate

Export Supply

Type:PS80-HM-CN Flow Range :0-80L/S Automatic Nozzle (0-1250GPM) Working Pressure : 10 bar Max Reach @ Max Flow : 80m Range Of Motion : -90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever Action...



Key Highlights

Category	Manual Operated Fire Monitor
Standard	EN
Material	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever ...
Weight / Size	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Manual Operated Fire Monitor	Model / SKU	Aluminum-Manual-Fire-Monitor-PS80-HM-CN
Standard	EN	Material	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever Action Rotational Lock Material (body) : Aluminum Material (Gear) : Aluminum Material (nozzle) : Brass, Adjustable Material (handwheel) : plastic Pump Requirement For Minimum Performance : 80L/S@ 8 bar Pipe dimensions for installation :
Weight / Size	-90°~+90°Vert , 360°Rot Max Fog Angle : 120° Horizontal Control : Lever Action Rotational Lock Material (body) : Aluminum Material (Gear) : Aluminum Material (nozzle) : Brass, Adjustable Material (handwheel) : plastic Pump Requirement For Minimum Performance : 80L/S@ 8 bar Pipe dimensions for installation :	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Aluminum Manual Fire Monitor PS80-HM-CN:

Type:PS80-HM-CN
 Flow Range :0-80L/S Automatic Nozzle (0-1250GPM)
 Working Pressure : 10 bar
 Max Reach @ Max Flow : 80m
 Range Of Motion : -90°~+90°Vert , 360°Rot
 Max Fog Angle : 120°
 Horizontal Control : Lever Action Rotational Lock
 Material (body) : Aluminum
 Material (Gear) : Aluminum
 Material (nozzle) : Brass, Adjustable
 Material (handwheel) : plastic
 Pump Requirement For Minimum Performance : 80L/S@ 8 bar
 Pipe dimensions for installation : 4 Inch
 Monitor Inlet : DN100 flange
 Monitor Outlet : 2.5 inch (65mm)
 Paint : Fire Red

