

MARINE WINDLASS

Anchor Windlass and Mooring Winch

General description The combined and capstan are for heaving, launching and mooring, which are in accordance with ISO4568-1986<>. They are driven by hand, electric, hydraulic and diesel engine. M...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	ISO
Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Marine Windlass	Model / SKU	Anchor-Windlass-and-Mooring-Winch
Standard	ISO	Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

■ General description

■ Main Parameter

General description

The combined and capstan are for heaving, launching and mooring, which are in accordance with ISO4568-1986<>. They are driven by hand, electric, hydraulic and diesel engine.

Main Parameter

Chain Dia (mm)	Working Load (kN)	Working Speed (m/min)	Mooring Pull (kN)	Mooring Speed (m/min)	Drun Capacity (Φ mm x m)	Motor Power (kW)	
						Electric	Hydrau lic
14/16/17.5	8.3/10.9/13.0	≥9	8	≥2	Φ11 x100	4.3/1.7	5.5
19/20.5/22	15.3/17.9/20.6	≥9	15	≥2	Φ13x120	8.5/3.5	7.5
24/26	24.5/28.7	≥9	20	≥2	Φ15x120	8.5/3.5	11
28/30	33.3/38.3	≥9	30	≥2	Φ18x150	11/11/7.5	15
32/34/36	43.5/49.1/55.1	≥9	40	≥2	Φ20.5x150	16/16/11	22
38/40/42	61.4/68.0/75.0	≥9	50	≥2	Φ20.5x150	22/22/16	30
44/46/48	82.3/89.9/97.9	≥9	60	≥2	Φ26 x 200	30/30/22	37
50/52/54	106.3/114.9/123.9	≥9	60	≥5	Φ26 x 200	30/30/22	45
56/58/60	133.3/143.0/153	≥9	80	≥5	Φ 26 x 200	45/45/30	55
62/64	163.4/174.1	≥9	80	≥5	Φ30 x 200	45/45/30	55
66/68	185.1/196.5	≥9	100	≥5	Φ30x200	45/45/30	75
70/73	208.3/226.5	≥9	120	≥5	Φ32.5x200	60/60/45	75
76/78	245.5/258.6	≥9	125	≥5	Φ32.5x200	60/60/45	90
81/84	311.7/335.2	≥9	140	≥5	Φ36 x 200	75/75/36	110
87/90	359.5/384.8	≥9	150	≥5	Φ38x200	75/75/36	120
92/95	402.0/428.7	≥9	200	≥5	Φ40x 200	85/85/64	130
97/100	446.9/475.0	≥9	250	≥5	Φ42x 200	100/100/50	150
105/107	523.7/543.8	≥9	300	≥5	Φ44x 200	110/110/55	180
112/114	595.8/617.3	≥9	350	≥5	Φ48x 200	132/132/66	200
120/122	684/707	≥9	400	≥5	Φ52x 250	/	250
124/127	730.4/766.1	≥9	450	≥5	Φ56 x 250	/	315
130/132	802.8/827.6	≥9	500	≥5	Φ58x 250	/	315
137/142	891.5/957.8	≥9	550	≥5	Φ62x 250	/	350