

PIPE FITTING

B12 Metal Elastic Support

Product Description: Applicable range: suitable for vertical and horizontal exhaust pipe.
Performance Parameters And Lectotype: ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Pipe Fitting
Standard	EN
Material	Special rubber
Weight / Size	Type Rated Vertical Load N(kgf) Deformation Under Rated Vertical Load(mm...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Pipe Fitting	Model / SKU	B12-Metal-Elastic-Support
Standard	EN	Material	Special rubber
Weight / Size	Type Rated Vertical Load N(kgf) Deformation Under Rated Vertical Load(mm) Natural Frequency(HZ) Damping Ratio C/Cc Vibration Test Ref.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- Product Description:
- Performance Parameters And Lectotype:
- Outline Dimension:

Product Description:

Applicable range: suitable for vertical and horizontal exhaust pipe.

Performance Parameters And Lectotype:

Type	Rated Vertical Load N(kgf)	Deformation Under Rated Vertical Load(mm)	Natural Frequency(HZ)	Damping Ratio C/Cc	Vibration Test Ref. Standard.
A10	300-7000 (30-700)	1.0-5.0	15-20 (swing input: Diameter 0.3mm	0.15~0.20	MIL-STD-167-I Michanical Vibration Of Ship Equipment
B12	500-9000 (50-900)	0.8-4.0	18-25 (swing input: Diameter 0.3mm	0.15~0.20	
B14	2500-70000 (250-7000)	2.5-5.8		0.15~0.20	
C12	500-9000 (50-900)	1.5-6.5	3-18 (swing input: Diameter 0.3mm	0.15~0.20	
C14	2500-70000 (250-7000)	3.0-6.5		0.15~0.20	
D21	500-5000 (50-500)	1.8-6.0	15-23 (swing input: Diameter 0.4mm	0.15~0.20	
D41	2500-30000 (250-3000)	3.5-6.0		0.15~0.20	

Outline Dimension:

Type	A	B	D1	D2	d1	d2	d3	h1	h2	h3	h4	Weight(kg)
A10	70	98	69	60	12.5	8	8	~53	17	10	-	0.8
B12	100	130	82	90	12.5	10	10	~71	31	13	-	1.9
B14	170	220	170	188	17	12	12	~97	55	16	-	10
C12	100	130	82	90	12.5	10	10	~100	54	13	-	2.2
C14	170	220	170	188	17	12	12	~125	80	16	-	13
D21	100	130	82	90	12.5	10	10	~73	90	46	13	2.2
D41	170	220	170	188	17	12	12	~97	112	80	13	13



