

TWISTLOCK

BD-E1 55 Degree Dovetail Twistlock

BREAKING LOAD:Shear 420KN, Tension:500KN SAFE WORKINGLOAD:Shear 210KN, Tension:250KN TOTAL WEIGHT 6.4KGS MATERIAL:HEAT TREATABLE STEEL FINISH:HOT DIP GALVANISED

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                                                             |
|---------------|-----------------------------------------------------------------------------|
| Category      | Twistlock                                                                   |
| Standard      | EN                                                                          |
| Material      | BREAKING LOAD:Shear 420KN, Tension:500KN SAFE WORKING LOAD:Shear 210KN, ... |
| Weight / Size | BREAKING LOAD:Shear 420KN, Tension:500KN SAFE WORKING LOAD:Shear 210KN, ... |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                  |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

| Technical Specifications |                                                                                                                                                                      |             |                                                                                                                                                                      |
|--------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category                 | Twistlock                                                                                                                                                            | Model / SKU | BD-E1-55-Degree-Dovetail-Twistlock                                                                                                                                   |
| Standard                 | EN                                                                                                                                                                   | Material    | BREAKING LOAD:Shear 420KN, Tension:500KN SAFE<br>WORKING LOAD:Shear 210KN, Tension:250KN TOTAL WEIGHT 6.4KGS MATERIAL:HEAT TREATABLE STEEL FINISH:HOT DIP GALVANISED |
| Weight / Size            | BREAKING LOAD:Shear 420KN, Tension:500KN SAFE<br>WORKING LOAD:Shear 210KN, Tension:250KN TOTAL WEIGHT 6.4KGS MATERIAL:HEAT TREATABLE STEEL FINISH:HOT DIP GALVANISED | Surface     | BREAKING LOAD:Shear 420KN, Tension:500KN SAFE<br>WORKING LOAD:Shear 210KN, Tension:250KN TOTAL WEIGHT 6.4KGS MATERIAL:HEAT TREATABLE STEEL FINISH:HOT DIP GALVANISED |
| Certificate              | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                                                                                                           | Warranty    | 12 Months unless specified otherwise                                                                                                                                 |
| Origin                   | China                                                                                                                                                                |             |                                                                                                                                                                      |

## China BD-E1 55 Degree Dovetail Twistlock:

BREAKING LOAD:Shear 420KN, Tension:500KN  
SAFE WORKING LOAD:Shear 210KN, Tension:250KN

TOTAL WEIGHT 6.4KGS

MATERIAL:HEAT TREATABLE STEEL

FINISH:HOT DIP GALVANISED