

JIS NEEDLE VALVE

Brass Needle Valve with Ring Joint Nut on Both Ends

ISO9001 Supplier

Class Certificate

Export Supply

Brass Needle Valve is used to connect the copper tubing, control the flow of liquids or gas requiring close regulating. Technical Specification: 1. Applicable temperature will be -20°C to 100°C 2. M...



Key Highlights

Category	JIS Needle Valve
Standard	EN
Material	Brass
Weight / Size	3.43Mpa (35kgf/cm2) 3.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	JIS Needle Valve	Model / SKU	Brass-Needle-Valve-with-Ring-Joint-Nut-on-Both-Ends
Standard	EN	Material	Brass
Weight / Size	3.43Mpa (35kgf/cm2) 3.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China Brass Needle Valve with Ring Joint Nut on Both Ends:
 - Main Material:
- Technical Specification:
 - Main Size:

China Brass Needle Valve with Ring Joint Nut on Both Ends:

Brass Needle Valve is used to connect the copper tubing, control the flow of liquids or gas requiring close regulating.

Technical Specification:

- 1. Applicable temperature will be -20°C to 100°C
- 2. Max Pressure: 3.43Mpa (35kgf/cm2)
- 3. Recommended for use at less than 80% of max load pressure at temperature between 80°C and 100°C.

Main Material:

Body: Brass
Stem: Brass

Main Size:

IMPA	Nominal Size	OD of Tube	Thread	Length	Height
752101	6 x 1/4	6	PF-1/4	57	37
752102	8 x 3/8	8	PF-3/8	68	42
752103	10 x 3/8	10	PF-3/8	85	50
752104	12 x 1/2	12	PF-1/2	91	50
752105	14 x 1/2	14	PF-1/2	93	50