

CB MARINE STORM VALVE

Bronze Screw Down Vertical Storm Valve CB/T3477-92 Type B/BS

ISO9001 Supplier

Class Certificate

Export Supply

Marine Screw Down Vertical Storm Valve CB/T3477-92 is the ship side valve to discharge sewage or waste water and prevent outboard water pouring. It can be closed by the handwheel. Technical Specification: Des...



Key Highlights

Category	CB Marine Storm Valve
Standard	GB
Material	Bronze
Weight / Size	GB600 Type A- Straight Type, Flange size as per GB569 Type AS-Straight T...
Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS


We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	CB Marine Storm Valve	Model / SKU	Bronze-Screw-Down-Vertical-Storm-Valve-CB-T3477-92-Type-B-BS
Standard	GB	Material	Bronze
Weight / Size	GB600 Type A- Straight Type, Flange size as per GB569 Type AS-Straight Type, Flange size as per GB2501 Type B- Angle Type, Flange size as per GB569 Type BS-Angle Type, Flange size as per GB2501 Type Nominal Pressure (Mpa) Nominal Size (mm) Applicable medium A,AS,B,BS 0.1 50-150 sea water, fresh water & sewage Main Parts & Material:	Certificate	CCS, BV, ABS, GL, LR, DNV, NK,RINA, KR,IRS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	■ China Bronze Screw Down Vertical Storm Valve CB/T3477-92 Type B/BS:	■ Technical Specification:
	■ Main Parts & Material:	■ Main Size List(mm):

China Bronze Screw Down Vertical Storm Valve CB/T3477-92 Type B/BS:



Marine Screw Down Vertical Storm Valve CB/T3477-92 is the ship side valve to discharge sewage or waste water and prevent outboard water pouring. It can be closed by the handwheel.

Technical Specification:

Design Standard:CB/T3477-92

Test Standard: GB600

Type A- Straight Type, Flange size as per GB569

Type AS-Straight Type, Flange size as per GB2501

Type B- Angle Type, Flange size as per GB569

Type BS-Angle Type, Flange size as per GB2501

Type	Nominal Pressure (Mpa)	Nominal Size (mm)	Applicable medium
A,AS,B,BS	0.1	50-150	sea water, fresh water & sewage

Main Parts & Material:

Body-Bronze

Bonnet-Bronze

Disc-Bronze

Stem-Bronze

Clamp Material-Brass

Main Size List(mm):

Type A,B:

no min al dia met er	structure dimension							Thicknes s δ		flange connection dimension					bolt		hand wheel		Lift Rang e m	Weight(kg)			
																				cast steel		bronze	
	H	H 1	H 2	H 3	L	L 1	L 2	cast ste el	br on ze	D	D 1	D 2	b	d 0	n	Th .	Do	S		A	B	A	B
50	210	170	300	327	135	90	100	7.5	5	135	103	84	13	15	6	M14	80	11	40	12	13	10	11
65	240	200	350	382	142	110	120	8.0	6	155	123	104	14	15	6	M14	80	11	45	17	19	13	15
80	260	220	400	437	155	120	130	8.5	6	170	138	118	14	15	8	M14	80	11	45	22	24	19	21
100	280	250	450	493	172	130	143	9.0	6	190	158	138	14	15	8	M14	80	11	45	30	35	28	31
125	330	270	500	577	195	150	160	10.0	7	215	183	164	14	15	10	M14	80	11	65	44	50	40	46
150	360	310	550	637	213	165	174	11.0	7	240	208	190	14	15	12	M14	120	11	65	52	67	48	63

Type AS/BS:

no min al dia met er	structure dimension							Thicknes s δ		flange connection dimension					bolt		hand wheel		Lift Rang e m	Weight(kg)			
																				cast steel		bronze	
	H	H 1	H 2	H 3	L	L 1	L 2	cast ste el	bro nze	D	D 1	D 2	b	d 0	n	Th .	Do	S		A S	B S	A S	B S
50	210	170	360	327	135	90	100	8.0	5	140	110	90	16	14	4	M12	80	11	40	12	13	11	12
65	240	200	385	342	142	110	110	8.0	6	160	130	110	16	14	4	M12	80	11	45	17	19	14	16
80	260	220	400	370	155	122	120	9.0	6	190	150	128	18	18	4	M16	80	11	45	22	24	20	22
100	280	250	430	393	172	133	137	9.0	6	210	170	148	18	18	4	M16	80	11	45	30	35	29	33
125	330	270	465	407	195	156	160	10.0	7	240	200	178	20	18	8	M16	80	11	65	44	50	42	48
150	360	310	490	437	213	165	174	10.0	7	265	225	202	20	18	8	M16	120	11	65	52	67	50	64