

MARINE FIRE DOOR LOCK

C-2 Fire Protection Vessel Door Lock

This vessel door lock incorporates double bolts. single cylinder and master key mechanism. The bolt may be operated freely by lever handle at ordinary time. If the dead bolt is locked by keys outside or by kn...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fire Door Lock
Standard	DIN
Material	Suitable for steel or watertight doors about 40 mm in thickness.
Weight / Size	Size of C-2 Fire Protection Vessel Door Lock
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Fire Door Lock	Model / SKU	C-2-Fire-Protection-Vessel-Door-Lock
Standard	DIN	Material	Suitable for steel or watertight doors about 40 mm in thickness.
Weight / Size	Size of C-2 Fire Protection Vessel Door Lock	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China C-2 Fire Protection Vessel Door Lock:

This vessel door lock incorporates double bolts. single cylinder and master key mechanism.

The bolt may be operated freely by lever handle at ordinary time.

If the dead bolt is locked by keys outside or by knob inside, the lever handle will become immovable.

Water—proof cover can be used.

Suitable for steel or watertight doors about 40 mm in thickness.

Size of C-2 Fire Protection Vessel Door Lock

