

MARINE FIRE DOOR LOCK

C-2B Fire Protection Vessel Door Lock

This vessel door lock incorporates double bolt, single cylinder and master key mechanism, lock body width of 80mm. The bolt may be operated freely by lever handle at ordinary time. The dead bolt can be unlocked...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fire Door Lock
Standard	DIN
Material	Suitable for steel or watertight doors about 40 mm in thickness.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Fire Door Lock	Model / SKU	C-2B-Fire-Protection-Vessel-Door-Lock
Standard	DIN	Material	Suitable for steel or watertight doors about 40 mm in thickness.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China C-2B Fire Protection Vessel Door Lock:

This vessel door lock incorporates double bolt, single cylinder and master key mechanism, lock body width of 80mm. The bolt

may be operated freely by lever handle at ordinary time. The dead bolt can be unlocked by knob inside, and locked or unlocked

by keys outside. Water—proof cover can be used.

Suitable for steel or watertight doors about 40 mm in thickness.

