

SHIPBUILDING STEEL

C Type Hydraulic Press For Shipyard

C Type Hydraulic Press The machine is applicable to axial parts, profile calibration process, the axis and set workpieces'press mounting, even the simple plank parts to stretching, bending, stamping, molding, and dropping material and so on, also can pressure the general powder, plastic products.



Key Highlights	
Category	Shipbuilding Steel
Standard	DIN
Material	C Type Hydraulic Press The machine is applicable to axial parts, profil...
Weight / Size	Machine working environment 1) Temperature 0°C ~ 40°C 2) Humidity relati...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications			
Category	Shipbuilding Steel	Model / SKU	C-Type-Hydraulic-Press-For-Shipyard
Standard	DIN	Material	C Type Hydraulic Press The machine is applicable to axial parts, profile calibration process, the axis and set workpieces'press mounting, even the simple plank parts to stretching, bending, stamping, molding, and dropping material and so on, also can pressure the general powder, plastic products.
Weight / Size	Machine working environment 1) Temperature 0°C ~ 40°C 2) Humidity relative temperature below 90% 3) Voltage three phase 380 V (-15%, +15%) 50 Hz C Type Hydraulic Press Technical Specifications name 6.3 10 16 25 40 63 100 160 pressure KN 63 100 160 250 400 630 1000 1600 2000 3150 4000 5000 6300 8000 Max pressure Mpa 8 12.5 20 16 25 25 25 25 25 25 25 25 25 25 Block trave mm 250 250 400 400 400 500 600 700 700 800 800 900 900 900 Opening mouth mm 400 400 500 630 630 750 800 900 1000 1100 1250 1300 1500 1500 throat depth mm 200 200 250 350 350 320 400 420 450 800 1500 1500 1500 1500 1500 Block speed empty mm/s 80 80 120 100 80 working mm/s 18~20 20~22 18~20 18~20 18~20 18~20 15~20 10~12 return mm/s 55 50 50 75 75 100 100 100 Working table dimensions L-R mm 440 440 500 580 700 710 800 800 mm 380 380 450 570 570 600 700 700 Table height over the ground mm 700 700 710 710 710 810 800 800 900 400 400 400 400 400 400 Hole dimension mm φ100 φ100 φ100 Main power KW 3 3 4 5.5 5.5 7.5 7.5 15 22 22 2x22 2x22 2x22	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	C Type Hydraulic Press	C Type Hydraulic Press Technical Specifications
----------	------------------------	---

C Type Hydraulic Press

The machine is applicable to axial parts, profile calibration process, the axis and set workpieces'press mounting, even the simple plank parts to stretching, bending, stamping, molding, and dropping material and so on, also can pressure the general powder, plastic products.

Machine working environment

- 1) Temperature 0°C ~ 40°C
- 2) Humidity relative temperature below 90%
- 3) Voltage three phase 380 V (-15%, +15%) 50 Hz

C Type Hydraulic Press Technical Specifications

name		6.3		10		16		25		40		63		100		160
pressure	KN	63	100	160		250	400	630	1000	1600	2000	3150	4000	5000	6300	8000
Max pressure	Mpa	8	12.5	20		16	25	25	25	25	25	25	25	25	25	25
Block trave	mm	250	250	400		400	400	500	600	700	700	800	800	900	900	900
Opening mouth	mm	400	400	500		630	630	750	800	900	1000	1100	1250	1300	1500	1500
throat depth	mm	200	200	250		350	350	320	400	420	450	800	1500	1500	1500	1500
Block speed	empty	mm/s	80		80		120		100		80					
	working	mm/s	18~20	20~22		18~20		18~20		18~20		18~20		15~20		10~12
	return	mm/s	55	50		50		75		75		100		100		100
Working table dimensions	L-R	mm	440	440		500		580		700		710		800		800
	mm	380	380		450		570		570		600		700		700	
Table height over the ground		mm	700	700	710	710	710	810	800	800	900	400	400	400	400	400
Hole dimension	mm	φ100	φ100	φ100												
Main power	KW	3	3	4	5.5	5.5	7.5	7.5	7.5	15	22	22	2x22	2x22	2x22	