

LIFEBOAT AND RESCUE BOAT ACCESSORIES

CDHD-20/24III Marine Charging Power

Description: Marine charging power supply is a switching power supply multifunctional charging power supply using high frequency PWM or PFM modulation technology, with IGBT, field effect power tube and pulse width ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Lifeboat And Rescue Boat Accessories
Standard	DIN
Weight / Size	Eliminating the bulky and noisy power frequency transformer, the weight ...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Lifeboat And Rescue Boat Accessories	Model / SKU	CDHD-20-24-Marine-Charging-Power
Standard	DIN	Weight / Size	Eliminating the bulky and noisy power frequency transformer, the weight of the whole machine is only a quarter of the thyristor charging power supply.
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China CDHD-20/24III Marine Charging Power:
- Description:
- Techincal data:

China CDHD-20/24III Marine Charging Power:

Description:

Marine charging power supply is a switching power supply multifunctional charging power supply using high frequency PWM or PFM modulation technology, with IGBT, field effect power tube and pulse width or frequency modulation integrated controller as the main components.

1. Eliminating the bulky and noisy power frequency transformer, the weight of the whole machine is only a quarter of the thyristor charging power supply.
2. The power supply is provided with multiple functional module options. The whole machine adopts intelligent cooling, which can ensure the reliable operation of the power supply even in the high temperature cabin.
3. This charging power supply is a three-stage automatic charging power supply (constant current equalization charging --- constant voltage equalization charging --- floating charging). The entire process of charging the battery is first entered into equalization charging, and the constant current is automatically completed first, and then constant voltage , When the current drops to near zero, the balanced charging is completed, so that it (manual or automatic) will be transferred to "floating charging" to trickle to maintain the battery in a fully charged state.
4. CDHD series marine charging power supply has type approval certificate issued by China Classification Society.



Techincal data:

Specifications (Output current)			20~40A
Input	Rated voltage		Single-phase 220VAC、 Three-phase 380VAC、 Three-phase 440VAC
	Input range		Rated voltage $\pm 15\%$
	Input frequency		45~65HZ
	Efficiency		$\geq 87\%$
	Maximum current	Single-phase 220	< 50A
		Three-phase 380	< 30A
		Three-phase 440	< 27A
Output	Floating voltage		251VDC $\pm 2V$ (Can be adjusted according to customer requirements and battery specifications)
	Average voltage		268VDC $\pm 2V$ (Can be adjusted according to customer requirements and battery specifications)
	Average floating charge conversion current		Rated output current 10% $\pm 1A$
	Regulation accuracy		$\pm 1\%$
	Output ripple and noise		VPP $\leq 300mV$
Function	Alarm and protection functions		Input under voltage protection, input over voltage protection, output under voltage warning, output over voltage protection, output short circuit protection, output over current protection
	Standard functions		Public warning, fault passive dry contact port (contact limit specification: 32V / 1A)
	Optional functions		Input instructions, work instructions, fault instructions, current regulation
Working environment	Operating temperature		-15°C~+55°C
	Storage temperature		-25°C~+85°C
	Relative humidity		0~95% (Non-condensing)
	Atmospheric pressure		70kPa~106kPa
	Cooling method		Air-cooled
Standard range	Safety		IEC61000-4-2、 IEC61000-4-3、 IEC61000-4-4、 IEC61000-4-5、 IEC61000-4-6、 IEC60092-101、 IEC60068-2-11
	Conduction, radiation		CISPR16、 EN55022
	Certification		CCS Type approval

Others	Size (WxDxH) mm	360x520x190
	Weight	25kg
	Installation method	Wall mounted installation

Packing:

