

IEC 60092 STANDARD CABLE (CHINA TYPE)

ISO9001 Supplier

Class Certificate

Export Supply

CEPF86/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured)

CEPF86/NC Cable is tinned copper wire braided and fire-resistant marine power and control cable 0.6/1kv. Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 ...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/Mica Tape/EPR insulation/SHF1 sheath/Galvanized Steel Wire...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications			
Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CEPF86-NC-Fire-Resistant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
Standard	EN	Material	Tinned Copper/Mica Tape/EPR insulation/SHF1 sheath/Galvanized Steel Wire Braided/SHF1
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China CEPF86/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CEPF86/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CEPF86/NC Cable is tinned copper wire braided and fire-resistant marine power and control cable 0.6/1kv.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Tinned Copper Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Fire Resistant: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300

Feature

Halogen-free, Low Smoke, Fire-resistant.

Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.