

IEC 60092 STANDARD CABLE (CHINA TYPE)

ISO9001 Supplier

Class Certificate

Export Supply

CEPJ95/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured)

CEPJ95/SC is Galvanized Steel wire Braided and Flame Retardant Marine Power and Control Cable. Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 Insu...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/XLPE insulation/SHF 2 sheath/Galvanized Steel Wire Braided...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CEPJ95-SC-Flame-Retardant-Marine-Power-Lighting-Cable-0-6-1KV-Armoured
Standard	EN	Material	Tinned Copper/XLPE insulation/SHF 2 sheath/Galvanized Steel Wire Braided/SHF2
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Surface	Galvanized
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	■ China CEPJ95/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):	■ Cable Construction
	■ Standards	■ Cores & Size
	■ Application:	

China CEPJ95/SC Flame Retardant Marine Power & Lighting Cable 0/6/1KV(Armoured):



CEPJ95/SC is Galvanized Steel wire Braided and Flame Retardant Marine Power and Control Cable.

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Inner Covering: Halogen-free Thermoset Polyolefin(SHF2)

Armour : Galvanized Wire Braided

Outer Sheath : Halogen-free Thermoset Polyolefin(SHF2)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300

Application:

The cable is fixed installation, used for power, lighting and control in most area and open deck area in ship.