

# Jinbo Marine

Marine &amp; Offshore Equipment Datasheet

PRODUCT DATASHEET

## SEWAGE PUMP

## CGW Series Marine Inline Sewage Pump

ISO9001 Supplier

Class Certificate

Export Supply

CGW series non-clog single-stage pipeline sewage pump has the same level for inlet and outlet, vertical structure, small size, motor and pump coaxial, equipped with installation chassis, easy to install, impeller adop...



### Key Highlights

Category	Sewage Pump
Standard	EN
Weight / Size	CGW series non-clog single-stage pipeline sewage pump has the same level...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

### Technical Specifications

Category	Sewage Pump	Model / SKU	CGW-Series-Marine-Inline-Sewage-Pump
Standard	EN	Weight / Size	CGW series non-clog single-stage pipeline sewage pump has the same level for inlet and outlet, vertical structure, small size, motor and pump coaxial, equipped with installation chassis, easy to install, impeller adopts single (double) port, good performance.
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

#### CONTENTS

- China CGW Series Marine Inline Sewage Pump:

- Main Specification

## China CGW Series Marine Inline Sewage Pump:



CGW series non-clog single-stage pipeline sewage pump has the same level for inlet and outlet, vertical structure, small size, motor and pump coaxial, equipped with installation chassis, easy to install, impeller adopts single (double) port, good performance.

### Main Specification

Type	Capacity		Head (m)	Efficiency (%)	Power (kw)	Speed (r/min)	Voltage (V)	Current (A)	Port (mm)	Weight (kg)
	(m <sup>3</sup> /h)	(l/s)								
10-10-1	10	2.8	10	44	1	2900	380	3.2	50	29
15-7-1	15	4.2	7	47	1	2900	380	3.2	50	29
10-15-1.5	10	2.8	15	44	1.5	2900	380	4.3	50	32
15-10-1.5	15	4.2	10	47	1.5	2900	380	4.3	50	32
25-8-1.5	25	6.9	8	51	1.5	2900	380	4.3	50	32
15-20-2.2	15	4.2	20	47	2.2	2900	380	4.9	65	45
25-14-2.2	25	6.9	14	50	2.2	2900	380	4.9	65	45

40-10-2.2	4 0	1 1 . 1	10	54	2.2	2900	380	4.9	65	45
20-22-3	2 0	5 . 6	22	49	3	2900	380	6.4	65	45
30-16-3	1 6	4 . 4	16	52	3	2900	380	6.4	65	45
40-12-3	4 0	1 1 . 1	12	54	3	2900	380	6.4	65	45
20-25-4	2 0	5 . 6	25	49	4	2900	380	8.2	65	75
30-18-4	3 0	8 . 3	18	52	4	2900	380	8.2	65	75
40-15-4	4 0	1 1 . 1	15	54	4	2900	380	8.2	65	75
60-13-4	6 0	1 6 . 7	13	57	4	2900	380	8.2	65	75
25-30-5.5	2 5	6 . 9	30	52	5.5	1470	380	12	50	75
30-21-5.5	3 0	8 . 3	21	52	5.5	1470	380	12	100	175
45-18-5.5	4 5	1 2 . 5	18	55	5.5	1470	380	12	100	175
65-15-5.5	6 5	1 8 . 1	15	45	5.5	1470	380	12	100	175
70-14-5.5	7 0	1 9 . 4	14	58	5.5	1470	380	12	100	175

100-8-5.5	1 0 0	2 7 8	8	60	5.5	1470	380	12	100	175
20-40-7.5	2 0	5 6	40	51	7.5	2900	380	16	80	200
45-30-7.5	4 5	1 2 5	30	52	7.5	1470	380	16	100	200
50-27-7.5	5 0	1 3 9	27	55	7.5	1470	380	16	100	200
70-20-7.5	7 0	1 9 4	20	58	7.5	1470	380	16	100	200
100-13-7.5	1 0 0	2 7 8	13	60	7.5	1470	380	16	100	200
150-8-7.5	1 5 0	4 1 7	8	62	7.5	1470	380	16	150	200
45-32-11	4 5	1 2 5	32	55	11	1470	380	24.1	100	280
70-22-11	7 0	1 9 4	22	58	11	1470	380	24.1	100	280
100-16-11	1 0 0	2 7 8	16	59	11	1470	380	24.1	150	280
150-10-11	1 5 0	4 1 7	10	61	11	1470	380	24.1	150	280
70-32-15	7 0	1 9 4	32	58	15	1470	380	24.1	100	280

100-22-15	1 0 0	2 7 .	22	59	15	1470	380	24.1	100	280
-----------	-------------	-------------	----	----	----	------	-----	------	-----	-----