

IEC 60092 STANDARD CABLE (CHINA TYPE)

CHEPF96/SC Flame Retardant Marine
Telecommunication
Cable250V(Screened)

ISO9001 Supplier

Class Certificate

Export Supply

CHEPF96/SC Cable is galvanized steel wire braided Marine Telecommunication & Instrument Cable 150/250V. Cable Construction Conductor: Stranded Tinned Anneal Copper. IEC 60228 Clas...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/XLPE insulatio/Galvanized Steel Wire Braided/SHF1 Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CHEPF96-SC-Flame-Retardant-Marine-Telecommunication-Cable250V-Screened
Standard	EN	Material	Tinned Copper/XLPE insulatio/Galvanized Steel Wire Braided/SHF1 Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Surface	galvanized
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China CHEPF96/SC Flame Retardant Marine Telecommunication Cable250V(Screened):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CHEPF96/SC Flame Retardant Marine Telecommunication Cable250V(Screened):



CHEPF96/SC Cable is galvanized steel wire braided Marine Telecommunication & Instrument Cable 150/250V.

Cable Construction

Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Screened: Pair Screened by Aluminium Polyester

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Galvanized Steel Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,24P,27P, 30P, 33P,37P,

1T, 2T,3T,4T,5T,7T,10T,12T,14P,16T,19T,24T,27T, 30T, 33T,37T

Size (sqmm): 0.75, 1, 1.5, 2.5.

Feature

Halogen-free, Low Smoke, Flame retardant

Application:

The cable is fixed installation, used for telecommunication, computer and information processing unit of shipboard and naval ship.