

IEC 60092 STANDARD CABLE (CHINA TYPE)

CHEPJ85/SC Flame Retardant Marine
Telecommunication
Cable250V(Screened)

ISO9001 Supplier

Class Certificate

Export Supply

CHEPJ85/SC Cable is tinned copper wire screened Marine Telecommunication & Instrument Cable 150/250V. Cable Construction Conductor: Stranded Tinned Anneal Copper. IEC 60228 ...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/EPR insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CHEPJ85-SC-Flame-Retardant-Marine-Telecommunication-Cable250V-Screened
Standard	EN	Material	Tinned Copper/EPR insulation/SHF2 sheath/Tinned Copper Wire Braided/SHF2 sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China CHEPJ85/SC Flame Retardant Marine Telecommunication Cable250V(Screened):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CHEPJ85/SC Flame Retardant Marine Telecommunication Cable250V(Screened):



CHEPJ85/SC Cable is tinned copper wire screened Marine Telecommunication & Instrument Cable 150/250V.

Cable Construction

Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Screened: Pair Screened by Aluminum Polyester with copper wire

Inner Covering: Halogen-free Thermoset Polyolefin(SHF2)

Armour : Tinned Copper Wire Braided

Outer Sheath : Halogen-free Thermoset Polyolefin(SHF2)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,24P,27P, 30P, 33P,37P,

1T, 2T,3T,4T,5T,7T,10T,12T,14P,16T,19T,24T,27T, 30T, 33T,37T

Size (sqmm): 0.75, 1, 1.5, 2.5.

Feature

Halogen-free, Low Smoke, Flame retardant

Application:

The cable is fixed installation, used for telecommunication, computer and information processing unit of shipboard and naval ship.