

IEC 60092 STANDARD CABLE (CHINA TYPE)

ISO9001 Supplier

Class Certificate

Export Supply

CHJPF86/SC Flame Retardant Marine Telecommunication Cable250V(Screened)

CHJPF86/SC Cable is tinned copper wire screened and Flame Retardant Marine Telecommunication & Instrument Cable 150/250V. Cable Construction & Conductor: Stranded Ti...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	EN
Material	Tinned Copper/XLPE insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF...
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CHJPF86-SC-Flame-Retardant-Marine-Telecommunication-Cable250V-Screened
Standard	EN	Material	Tinned Copper/XLPE insulation/SHF1 sheath/Tinned Copper Wire Braided/SHF1
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	LR, ABS,BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China CHJPF86/SC Flame Retardant Marine Telecommunication Cable250V(Screened):
- Standards
- Feature
- Cable Construction
- Cores & Size
- Application:

China CHJPF86/SC Flame Retardant Marine Telecommunication Cable250V(Screened):



CHJPF86/SC Cable is tinned copper wire screened and Flame Retardant Marine Telecommunication & Instrument Cable 150/250V.

Cable Construction

Conductor: Stranded Tinned Anneal Copper. IEC 60228 Class 2

Insulation : EPR Insulation

Screened: Pair Screened by Aluminum Polyester with copper wire

Inner Covering: Halogen-free Thermoplastic Polyolefin(SHF1)

Armour : Tinned Copper Wire Braided

Outer Sheath : Halogen-free Thermoplastic Polyolefin(SHF1)

Standards

Design : IEC 60092-350, 376

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60332-1 & IEC 60332-3 Category A

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1P, 2P,3P,4P,5P,7P,10P,12P,14P,16P,19P,24P,27P, 30P, 33P,37P,

1T, 2T,3T,4T,5T,7T,10T,12T,14P,16T,19T,24T,27T, 30T, 33T,37T

Size (sqmm): 0.75, 1, 1.5, 2.5.

Feature

Halogen-free, Low Smoke, Flame retardant

Application:

The cable is fixed installation, used for telecommunication, computer and information processing unit of shipboard and naval ship.