

IEC 60092 STANDARD CABLE (CHINA TYPE)

CJPF/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(No Armoured)

ISO9001 Supplier

Class Certificate

Export Supply

CJPF/NC Type Cable is Fire-Resistant Marine Power & Control Cable (No armoured)
Cable Construction Conductor: Tinned Copper. IEC 60228 Class 2 Mica Tape In...



Key Highlights

Category	IEC 60092 Standard Cable (China Type)
Standard	DIN
Material	Tinned Copper/Mica Tape/XLPE insulation/SHF1 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:
Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	IEC 60092 Standard Cable (China Type)	Model / SKU	CJPF-NC-Fire-Resistant-Marine-Power-Lighting-Cable-0-6-1KV-No-Armoured
Standard	DIN	Material	Tinned Copper/Mica Tape/XLPE insulation/SHF1 Outer Sheath
Weight / Size	IEC 61034-1, IEC61034-2 Cores & Size Cores:	Certificate	ABS, LR, BV, GL, RINA, DNV, NK, KR, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

- China CJPF/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(No Armoured):
- Standards
- Features
- Cable Construction
- Cores & Size
- Delivery

China CJPF/NC Fire Resistant Marine Power & Lighting Cable 0/6/1KV(No Armoured):



CJPF/NC Type Cable is Fire-Resistant Marine Power & Control Cable (No armoured)

Cable Construction

Conductor: Tinned Copper. IEC 60228 Class 2

Mica Tape

Insulation : XLPE Insulation

Inner Covering: None

Armour : None

Outer Sheath : Halogen-free Cross Linked Thermoset Polyolefin(SHF2)

Standards

Design : IEC 60092-350, 353

Insulation Material : IEC 60092 -351

Sheath Material : IEC 60092-359

Flammability: IEC 60331

Halogen--free: IEC60754-1, IEC60754-2

Smoke Emission: IEC 61034-1, IEC61034-2

Cores & Size

Cores: 1, 2,3,4,5,7,10,12,14,16,19,24,37

Size (sqmm): 1.5, 2.5, 4, 6, 10, 16, 25, 35, 50, 70, 95, 120, 150, 180, 240, 300

Features

Halogen-free, Low Smoke, Flame retardant

Delivery

We can delivery around the world according to Incoterms 2010.