

CENTRIFUGAL PUMP

CLT Series Marine Vertical Centrifugal Pump 40CLT-100

ISO9001 Supplier

Class Certificate

Export Supply

CLT series marine vertical centrifugal pump can be used to convey sea water or fresh water or other liquid not exceed 80°C in temperature. They can also be used to deliver ballast tank water of the boats and ships serve t...



Key Highlights

Category	Centrifugal Pump
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Centrifugal Pump	Model / SKU	CLT-Series-Marine-Vertical-Centrifugal-Pump-40CLT-100
Standard	DIN	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China CLT Series Marine Vertical Centrifugal Pump 40CLT-100:

CLT series marine vertical centrifugal pump can be used to convey sea water or fresh water or other liquid not exceed 80°C in temperature. They can also be used to deliver ballast tank water of the boats and ships serve the purpose of cooling, fire control,life water etc. According to the user needs CLTR series marine vertical centrifugal pump can supply the hot water pump that don't exceed 130°C in temperature. CLTY series marine vertical oil centrifugal pump major used to shipping deliver clean oil, it can deliver light diesel oil, petrol and other chemical products similar in physical and chemical, as for combustibile dangerous medium should choose spark-proof motor or use bulkhead measure to ensure production safely.

Main Technical Data				
Model	Flow rate Q m ³ /h	Lift H (m)	Rev speed r/min	Motor power (KW)
40CLT-100	4.5/5.6/6.66	12.8/10/8	2900	0.75
40CLT-100J	2.25/2.8/3.33	3.2/2.5/2	1450	0.55
40CLT-125	4.5/5.6/6.66	19.5/16/14.4	2900	0.75
40CLT-125J	2.25/2.8./3.33	4.9/4/3.6	1450	0.55
40CLT-160	4.5/5.6/6.66	30.5/28/26.3	2900	1.1
40CLT-160J	2.25/2.8/3.33	7.5/7/6.6	1450	0.55
40CLT-200	4.5/5.6/6.66	49/46.5/42	2900	3
40CLT-200J	2.25/2.8/3.33	12.2/11.6/10.5	1450	0.55
50CLT-125	6.2/10.4/12.5	15.2/13.8/12.8	2900	1.1
50CLT-125J	3.1/5.2/6.2	3.7/3.5/3.2	1450	0.55
50CLT-160	5.4/9/10.8	17.9/16.7/15.4	2900	1.5
50CLT-160J	2.7/4.6/5.4	4.4/4.2/3.9	1450	0.55
50CLT-200	6.5/10.9/13	39.6/37.7/36.2	2900	4
50CLT-200J	3.3/5.5/6.5	13.1/12.5/12	1450	0.55
50CLT-250	6.0/10.0/12.0	52.5/51.5/50.2	2900	5.5
50CLT-250J	3.0/5.0/6.0	13.1/12.8/12.5	1450	0.75
65CLT-125	11.3/18.9/22.6	12.4/11.4/10.5	2900	1.5
65CLT-125J	5.7/9.4/11.3	3/2.8/2.7	1450	0.55
65CLT-160	12/20.1/24.1	22.5/20.6/19.3	2900	3
65CLT-160J	6.0/1.0/12.0	5.7/5.2/4.6	1450	0.55
65CLT-200	12.8/21.3/25.5	38.3/36.1/34	2900	5.5
Alao have bigger pumps, pls contact us for more information.				

