RUBBER SHEET

CR Neoprene Rubber Sheet

ISO9001 Supplier

Class Certificate

Export Supply

CR Neoprene Rubber Sheet Specification: 0.8 to 50mm thickness.   0.2 to 3 m width.   1 to 20 m length. Density:1.3 to 1.5g/cm3 . Tensile strength: 350 to 450psi E...



Key Highlights

Category	Rubber Sheet
Standard	EN
Material	100% to 300% Hardness:40 to 80 ±5 Shore-A Application: Petrochemicals ...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Rubber Sheet	**Model / SKU**	CR-Neoprene-Rubber-Sheet
Standard	EN	**Material**	100% to 300% Hardness:40 to 80 ±5 Shore-A Application: Petrochemicals industry, chemical parts, steel mills, metal to rubber adhension, insulation from oils,acids,alkali,heat.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	**Warranty**	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China CR Neoprene Rubber Sheet:
- Features:
- Application:

China CR Neoprene Rubber Sheet:

CR Neoprene Rubber Sheet

Specification: 0.8 to 50mm thickness. 0.2 to 3 m width. 1 to 20 m length.

Density:1.3 to 1.5g/cm3 .

Tensile strength: 350 to 450psi

Elongation: 100% to 300%

Hardness:40 to 80 ±5 Shore-A

Application:

Petrochemicals industry, chemical parts, steel mills, metal to rubber adhension, insulation from oils,acids,alkali,heat.

Features:

Good tensile strength, excellent resistance to ozone,oxidation and sunlight.

Low resilence,ideal for vibration damping and shock absorption applications.

Resistance to abrasion and compression set.

High resistant to mineral acids,alkali and aqueous acids.