

CHAIN SLING

Crack detectable RL Round Sling

Description In case abnormity, light beam can be used to detect whether the interior of the sling is ruptured or not. Technical Data Products code Workin...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chain Sling
Standard	EN
Weight / Size	Technical Data Products code Working load limit (kg) Approximate thickne...
Certificate	CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Chain Sling	Model / SKU	Crack-detectable-RL-Round-Sling
Standard	EN	Weight / Size	Technical Data Products code Working load limit (kg) Approximate thickness (mm) Approximate width (mm) Min length (m) Max length (m) RL1/2 500 4 50 0.5 RL001 1000 6 50 0.5 RL002 2000 8 60 0.5 RL003 3000 9 70 0.5 RL004 4000 11 70 0.5 RL005 5000 13 85 0.5 RL006 6000 13 85 1 To be customized RL008 8000 13 120 1 RL010 10000 14 120 2 RL012 12000 15 130 2 RL015 15000 18 130 2 RL020 20000 20 140 2.5 RL025 25000 24 140 2.5 RL030 30000 32 145 2.5 RL040 40000 40 150 2.5 RL050 50000 45 175 2.5 RL060 60000 65 205 4 RL080 80000 70 250 4 RL100 100000 80 290 4
Certificate	CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	Description Technical Data
----------	--

Description

In case abnormity, light beam can be used to detect whether the interior of the sling is ruptured or not.

Technical Data

Products code	Working load limit (kg)	Approximate thickness (mm)	Approximate width (mm)	Min length (m)	Max length (m)
RL1/2	500	4	50	0.5	
RL001	1000	6	50	0.5	
RL002	2000	8	60	0.5	
RL003	3000	9	70	0.5	
RL004	4000	11	70	0.5	
RL005	5000	13	85	0.5	
RL006	6000	13	85	1	To be customized

RL008	8000	13	120	1
RL010	10000	14	120	2
RL012	12000	15	130	2
RL015	15000	18	130	2
RL020	20000	20	140	2.5
RL025	25000	24	140	2.5
RL030	30000	32	145	2.5
RL040	40000	40	150	2.5
RL050	50000	45	175	2.5
RL060	60000	65	205	4
RL080	80000	70	250	4
RL100	100000	80	290	4