

MARINE COMMUNICATION EQUIPMENT

ISO9001 Supplier

Class Certificate

Export Supply

CY-VH02 Marine VHF Interphone

CY-VH02 Marine VHF Interphone with excellent waterproof function,use it 1 meter under water,it can keep watertight in 5 minutes,good corrosion resistance,it can adapt the severe environment on the vessel,easy to operate,...



Key Highlights

Category	Marine Communication Equipment
Standard	EN
Weight / Size	< +1.5kHz Size (W x H x D):
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Communication Equipment	Model / SKU	CY-VH02-Marine-VHF-Interphone
Standard	EN	Weight / Size	< +1.5kHz Size (W x H x D):
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China CY-VH02 Marine VHF Interphone:

CY-VH02 Marine VHF Interphone with excellent waterproof function,use it 1 meter under water,it can keep watertight in 5 minutes,good corrosion resistance,it can adapt the severe environment on the vessel,easy to operate,unskilled person can use it too,and it can be operate by one hand only.Good property,High reliable.

- Frequency Range: 154-163MHz
- Channel Spacing: 25kHz (12.5kHz optional)
- Working Temperature: -20°C to +55°C
- Sensitivity: 0.18μV for 12 dB SINAD
- Adjacent Channel Power: > 70 dB
- Blocking: > 70 dB
- Spurious Response: > 70 dB

Modulation Distortion: < 5%

intermodulation Immunity: > 68 dB

Radio Frequency Output Power : 1W (Lo)/5W (Hi)

Frequency Tolerance : < +1.5kHz

Size (W x H x D): 56 x 133 x 27.5 mm (not include antenna and button)

Weight: 280 g (include battery,button and antenna)