

ELECTRIC HEATER

D25D Marine Tumble Dryer

D25D Marine Tumble Dryer Product introduction: 1.The shell adopts stainless steel, durable; 2.The high density of imported stainless steel stamping forming the inner cylinder, the clothes...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Electric Heater
Standard	DIN
Material	SS304
Weight / Size	Model Dimension(mm) Capacity(kg) Power (kw) Volts(v) HZ N/W(kg) D22D 76...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Electric Heater	Model / SKU	D25D-Marine-Tumble-Dryer
Standard	DIN	Material	SS304
Weight / Size	Model Dimension(mm) Capacity(kg) Power (kw) Volts(v) HZ N/W(kg) D22D 760X850X1540 10 8.6 380V/415V/440V/480V-3P 50/60Hz 130 D25D 760X930X1540 12 10.5 380V/415V/440V/480V-3P 50/60Hz 150 D35D 760X1050X1540 15 12.5 380V/415V/440V/480V-3P 50/60Hz 170 D45D 910X1150X1920 20 16.5 380V/415V/440V/480V-3P 50/60Hz 230	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS

☒ Product introduction:

☐ Technical data:

Product introduction:

- 1.The shell adopts stainless steel, durable;
- 2.The high density of imported stainless steel stamping forming the inner cylinder, the clothes wear small, high clothes drying efficiency;
- 3.The precision machining shaft seat system, high stability and low operation noise;
- 4.The large caliber loading door mechanism, convenient for taking and placing clothes;
- 5.The efficient air heat exchanger system, effectively reduce the energy consumption;
- 6.The high quality stainless steel electric heating tube, longer service life;
- 7.It can remove the installation foot.

Technical data:

Model	Dimension(mm)	Capacity(kg)	Power (kw)	Volts(v)	HZ	N/W(kg)
D22D	760X850X1540	10	8.6	380V/415V/440V/480V-3P	50/60Hz	130
D25D	760X930X1540	12	10.5	380V/415V/440V/480V-3P	50/60Hz	150
D35D	760X1050X1540	15	12.5	380V/415V/440V/480V-3P	50/60Hz	170
D45D	910X1150X1920	20	16.5	380V/415V/440V/480V-3P	50/60Hz	230