

HANGER AND ELASTIC SUPPORT

Deck Elastic Conduit

The Elastic Conduit is a supporter for exhaust pipe which is through the top of the funnel, it can level off the exhaust pipe in radial direction, it also for long exhaust pipe as a supporter. The elastic elements is ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Hanger And Elastic Support
Standard	ISO
Material	The elastic elements is stainless mesh, steel mesh have a good elasticit...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications

Category	Hanger And Elastic Support	Model / SKU	Deck-Elastic-Conduit
Standard	ISO	Material	The elastic elements is stainless mesh, steel mesh have a good elasticity, effect of vibration isolation and strong sympathetic vibration resistance performance, and it also can absorb the thermal deformation.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China Deck Elastic Conduit:
- Deck Elastic Conduit Main Specifications

China Deck Elastic Conduit:

The Elastic Conduit is a supporter for exhaust pipe which is through the top of the funnel, it can level off the exhaust pipe in radial direction, it also for long exhaust pipe as a supporter. The elastic elements is stainless mesh, steel mesh have a good elasticity, effect of vibration isolation and strong sympathetic vibration resistance performance, and it also can absorb the thermal deformation.

Deck Elastic Conduit Main Specifications

Model	DN	A	B	C	D	H	H1
DG-108	100	108	174	140	330	140	30
DG-114	100	114	180	150	335	140	30
DG-140	125	140	206	180	360	140	30
DG-159	150	159	225	200	380	140	30
DG-168	150	168	234	210	390	140	30
DG-194	175	194	260	230	420	140	30
DG-219	200	219	285	260	440	140	30
DG-245	225	225	311	285	465	140	30
DG-273	250	273	339	310	495	140	30
DG-325	300	325	395	360	545	140	30
DG-362	350	362	432	400	585	140	30
DG-377	350	377	447	410	600	140	30
DG-426	400	426	496	460	650	140	30
DG-460	450	460	530	500	680	140	30
DG-480	450	480	550	520	700	140	30
DG-508	500	508	582	550	730	150	30
DG-530	500	530	604	570	750	150	30
DG-610	600	610	684	650	830	150	30
DG-630	600	630	704	670	850	150	30
DG-711	700	711	785	750	930	150	30
DG-720	700	720	794	760	940	150	30
DG-813	800	813	887	850	1035	150	30
DG-914	900	914	988	950	1135	150	30
DG-916	900	916	990	950	1140	150	30
DG-1016	1000	1016	1090	1050	1240	150	30
DG-1112	1100	1112	1186	1150	1335	150	30
DG-1116	1100	1116	1190	1150	1340	150	30

DG-1220	1200	1220	1294	1260	1440	150	30
DG-1306	1300	1306	1380	1340	1530	150	30
DG-1416	1400	1416	1490	1450	1640	150	30