

CONNECTORS

Detachable Chain Connecting Link C type

ISO9001 Supplier

Class Certificate

Export Supply

Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains. Main Specification: CHAIN SIZE A B ...



Key Highlights

|               |                                                                             |
|---------------|-----------------------------------------------------------------------------|
| Category      | Connectors                                                                  |
| Material      | 20MN2                                                                       |
| Weight / Size | Connecting Link C type is used for connecting the mooring lines for the ... |
| Certificate   | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                  |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                            |               |                                                                                                                    |
|-------------|--------------------------------------------|---------------|--------------------------------------------------------------------------------------------------------------------|
| Category    | Connectors                                 | Model / SKU   | Detachable-Chain-Connecting-Link-C-type                                                                            |
| Material    | 20MN2                                      | Weight / Size | Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains. |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty      | 12 Months unless specified otherwise                                                                               |
| Origin      | China                                      |               |                                                                                                                    |

CONTENTS

- China Detachable Chain Connecting Link C type:
- Main Specification:

## China Detachable Chain Connecting Link C type:



Connecting Link C type is used for connecting the mooring lines for the same size, widely used for mooring chains.

### Main Specification:

| CHAIN SIZE |                    | A   | B   | C  | D  | E  | F  | G  | WEIGHT |      | PROOF TEST | BREAK TEST |
|------------|--------------------|-----|-----|----|----|----|----|----|--------|------|------------|------------|
| m          | inches             | mm  | mm  | mm | mm | mm | mm | mm | kg     | lbs  | KGF        | KGF        |
| 13-16      | 1/2 - 5/8          | 95  | 63  | 22 | 16 | 19 | 21 | 12 | 0.5    | 1    | 14651      | 23668      |
| 19         | 3/4                | 114 | 74  | 24 | 19 | 22 | 24 | 13 | 1      | 2    | 21771      | 34020      |
| 21-22      | 13/16 - 7/8        | 133 | 86  | 28 | 22 | 25 | 28 | 16 | 1.5    | 3.5  | 29030      | 44452      |
| 24-25      | 15/16 - 1          | 152 | 102 | 35 | 25 | 29 | 31 | 17 | 2.3    | 5.1  | 38000      | 54300      |
| 27-29      | 1 - 1/16 - 1 - 1/8 | 172 | 114 | 40 | 29 | 32 | 35 | 19 | 3.3    | 7.3  | 49200      | 70400      |
| 30-32      | 1 - 3/16 - 1 - 1/4 | 191 | 127 | 44 | 32 | 36 | 39 | 21 | 4.6    | 10.1 | 59500      | 84900      |
| 33-35      | 1 - 5/16 - 1 - 3/8 | 210 | 140 | 48 | 35 | 40 | 43 | 23 | 6.2    | 13.7 | 70700      | 101300     |
| 36-38      | 1 - 7/16 - 1 - 1/2 | 229 | 152 | 53 | 38 | 43 | 47 | 26 | 7.9    | 17.4 | 83300      | 118900     |

|       |                    |     |     |    |    |    |    |    |          |              |        |        |
|-------|--------------------|-----|-----|----|----|----|----|----|----------|--------------|--------|--------|
| 40-42 | 1-9/16<br>- 1-5/8  | 248 | 165 | 57 | 42 | 47 | 50 | 28 | 10       | 2<br>2       | 102000 | 143400 |
| 43-44 | 1-11/16<br>- 1-3/4 | 267 | 178 | 62 | 45 | 50 | 56 | 30 | 12<br>.5 | 2<br>7.<br>6 | 111900 | 159900 |
| 46-48 | 1-13/16<br>- 1-7/8 | 286 | 191 | 64 | 48 | 55 | 60 | 32 | 14<br>.5 | 3<br>2       | 130000 | 185100 |
| 50-51 | 1-15/16<br>- 2     | 305 | 197 | 64 | 51 | 59 | 64 | 34 | 16<br>.3 | 3<br>5.<br>9 | 145400 | 207700 |
| 52-54 | 2-1/16<br>- 2-1/8  | 324 | 209 | 67 | 54 | 63 | 68 | 36 | 20       | 4<br>4.<br>1 | 162000 | 231500 |
| 56-58 | 2-3/16<br>- 2-1/4  | 343 | 222 | 71 | 58 | 66 | 71 | 38 | 23<br>.6 | 5<br>2       | 185400 | 265000 |
| 59-60 | 2-5/16<br>- 2-3/8  | 364 | 235 | 78 | 61 | 70 | 76 | 41 | 28       | 6<br>1.<br>7 | 199600 | 285200 |
| 62-64 | 2-7/16<br>- 2-1/2  | 381 | 246 | 79 | 64 | 74 | 79 | 43 | 32<br>.2 | 7<br>1       | 223000 | 319000 |
| 66-67 | 2-9/16<br>- 2-5/8  | 400 | 259 | 83 | 67 | 77 | 83 | 45 | 37       | 8<br>1.<br>6 | 242900 | 347000 |
| 68-70 | 2-11/16<br>- 2-3/4 | 419 | 271 | 87 | 70 | 81 | 87 | 47 | 45       | 9<br>9.<br>2 | 263500 | 376400 |
| 71-73 | 2-13/16<br>- 2-7/8 | 438 | 283 | 91 | 73 | 85 | 91 | 49 | 49       | 1<br>0<br>8  | 285000 | 407000 |
| 75-76 | 2-15/16<br>- 3     | 457 | 296 | 95 | 76 | 88 | 95 | 51 | 55       | 1<br>2<br>1  | 308200 | 440200 |

|         |                    |     |     |     |     |     |     |    |               |             |        |        |
|---------|--------------------|-----|-----|-----|-----|-----|-----|----|---------------|-------------|--------|--------|
| 78-79   | 3-1/16<br>- 3-1/8  | 476 | 308 | 99  | 79  | 92  | 99  | 53 | 63            | 1<br>3<br>9 | 332100 | 474500 |
| 81-83   | 3-3/16<br>- 3-1/4  | 495 | 320 | 103 | 83  | 96  | 103 | 55 | 73            | 1<br>6<br>1 | 360400 | 514800 |
| 84-86   | 3-5/16<br>- 3-3/8  | 514 | 333 | 107 | 86  | 99  | 107 | 57 | 80            | 1<br>7<br>6 | 384400 | 549100 |
| 87-89   | 3-7/16<br>- 3-1/2  | 533 | 345 | 111 | 89  | 103 | 111 | 60 | 93            | 2<br>0<br>5 | 409000 | 584300 |
| 90-92   | 3-9/16<br>- 3-5/8  | 553 | 357 | 115 | 92  | 107 | 115 | 62 | 97<br>.6      | 2<br>1<br>5 | 434800 | 621200 |
| 94-95   | 3-11/16<br>- 3-3/4 | 572 | 370 | 119 | 95  | 111 | 119 | 64 | 11<br>6.<br>2 | 2<br>5<br>6 | 462300 | 660100 |
| 97-98   | 3-13/16<br>- 3-7/8 | 591 | 382 | 128 | 98  | 114 | 123 | 66 | 12<br>3       | 2<br>7<br>1 | 490000 | 700000 |
| 100-102 | 3-15/16<br>- 4     | 610 | 394 | 132 | 102 | 118 | 127 | 68 | 13<br>1       | 2<br>8<br>9 | 522100 | 746000 |
| 105     | 4<br>1/8           | 629 | 419 | 147 | 105 | 127 | 132 | 70 | 17<br>5       | 3<br>8<br>6 | 550000 | 785000 |
| 111     | 4<br>3/8           | 667 | 456 | 167 | 111 | 138 | 140 | 75 | 20<br>8       | 4<br>5<br>9 | 607000 | 867200 |
| 114     | 4<br>1/2           | 686 | 480 | 190 | 114 | 147 | 144 | 77 | 22<br>7       | 5<br>0<br>0 | 637300 | 910900 |

For more information, please feel free to contact us.