

YACHT & BOAT CHAIN

DIN766 Stainless Steel Link Chain

Material: SS304, SS316 or SS316L Size: 2mm to 16mm Finish: Mirror Polished Size Table  
Size Inside Length Inside Width ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|               |                                 |
|---------------|---------------------------------|
| Category      | Yacht & Boat Chain              |
| Standard      | DIN                             |
| Material      | SS304, SS316 or SS316L          |
| Weight / Size | SS304, SS316 or SS316L<br>Size: |
| Certificate   | Mill Certificate                |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|               |                              |             |                                      |
|---------------|------------------------------|-------------|--------------------------------------|
| Category      | Yacht & Boat Chain           | Model / SKU | DIN766-Stainless-Steel-Link-Chain    |
| Standard      | DIN                          | Material    | SS304, SS316 or SS316L               |
| Weight / Size | SS304, SS316 or SS316L Size: | Surface     | 2mm to 16mm Finish:                  |
| Certificate   | Mill Certificate             | Warranty    | 12 Months unless specified otherwise |
| Origin        | China                        |             |                                      |

China DIN766 Stainless Steel Link Chain:



Material: SS304, SS316 or SS316L

Size: 2mm to 16mm

Finish: Mirror Polished

Size Table

| Size | Inside Length | Inside Width | Weight |
|------|---------------|--------------|--------|
| MM   | MM            | MM           | KG/M   |
| 2    | 12            | 3.5          | 0.07   |
| 3    | 16            | 5            | 0.163  |
| 4    | 16            | 5            | 0.32   |
| 5    | 18.5          | 6            | 0.5    |
| 6    | 18.5          | 7.2          | 0.8    |
| 7    | 22            | 8.4          | 1.1    |
| 8    | 24            | 9.6          | 1.4    |
| 9    | 27            | 10.8         | 1.8    |
| 10   | 28            | 12           | 2.3    |
| 11   | 31            | 13.2         | 2.68   |
| 12   | 36            | 14.6         | 3.11   |
| 13   | 36            | 15.6         | 3.8    |
| 16   | 45            | 19.2         | 5.7    |