

MARINE WINDLASS

Double gypsy Windlass

Double gypsy Windlass General description The windlass are for heaving, launching and mooring, which are in accordance with ISO4568-1986<math>\lt;math>. They are driven by hand, electric, hydraulic and diesel engine...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	ISO
Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Double-gypsy-Windlass
Standard	ISO	Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS	Warranty	12 Months unless specified otherwise
Origin	China		

China Double gypsy Windlass:

Double gypsy Windlass

General description

The windlass are for heaving, launching and mooring, which are in accordance with ISO4568-1986<math>\lt;math>. They are driven by hand, electric, hydraulic and diesel engine. Widely used onboard the ship, can be lift up two anchor at one time with easy operation and longer life period.

Main technical parameter

anchor chain diam	working load		over loading		loading support		nominal speed	Drum load	Nominal speed	Cable capacity	Mooring line load
(mm)	A M 2	A M 3	A M 2	A M 3	A M 2	A M 3	m/min	Kn	m/min	m	Kn
17.5	1 3	1 4. 6	1 9. 5	2 1. 9	8 0	1 1 5	9	10	10	Φ11x100	8
19	1 5. 3	1 7. 2	2 3	2 5. 8	9 5	1 3 5	9	15	10	Φ13x100	10
20	1 7. 9	2 0	2 6. 9	3 0	1 1 0	1 5 7	9	20	10	Φ13x100	10
22	2 0. 6	2 3	3 0. 9	3 4. 5	1 2 6	1 8 0	9	20	15	Φ15x100	15
24	2 4. 5	2 7. 4	3 6. 8	4 1. 1	1 4 9	2 1 4	9	20	15	Φ15x100	20
26	2 8. 7	3 2. 1	4 3. 1	4 8. 2	1 7 5	2 5 0	9	20	10	Φ22x100	20
28	3 3. 3	3 7. 2	5 0	5 5. 8	2 0 2	2 8 9	9	20	10	Φ22x120	20
30	3 8. 3	4 2. 8	5 7. 5	6 4. 2	2 3 1	3 3 0	9	30	10	Φ22x120	30
32	4 3. 5	4 8. 6	6 5. 3	7 2. 9	2 6 1	3 7 4	9	30	9	Φ20x120	30
34	4 9. 1	5 4. 9	7 3. 3	8 2. 4	2 9 4	4 2 1	9	40	9	Φ20x120	30
36	5 5. 1	6 1. 6	8 2. 7	9 2. 4	3 2 9	4 7 0	9	30	12	Φ20x120	30
38	6 1. 4	6 8. 9	9 2. 1	1 0 3. 4	3 6 5	5 2 2	9	40	15	Φ22x150	40
40	6 8	7 6	1 0 2	1 1 4	4 0 2	5 7 6	9	40	9	Φ22x150	40

42	7 5	8 3. 8	1 1 2. 5	1 2 5. 7	4 4 2	6 3 2	9	40	15	Φ22x150	50
44	8 2. 3	9 2	1 2 3. 5	1 3 8	4 8 3	6 9 1	9	50	15	Φ26x200	50
46	8 9. 9	1 0 0. 5	1 3 4. 9	1 5 0. 8	5 2 6	7 5 3	9	50	18	Φ26x200	50
48	9 7. 9	1 0 9. 4	1 4 6. 9	1 6 4. 1	5 7 0	8 1 6	9	60	10	Φ26x200	50
50	1 0 6. 3	1 1 8. 8	1 5 9. 5	1 7 8. 2	6 1 7	8 8 2	9	80	15	Φ26x200	50