

STEEL FIRE DOOR WITH WH

Double hollow metal door

1. 60min/90min/180mins fire proof with WH certificate 2. Double leafs with fireproof glasses 3. Panic bar, door closer,fireproof handle

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Steel fire door with WH
Material	Cold roll steel & Galvanized steel
Certificate	Warnock Hersey, ITS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Steel fire door with WH	Model / SKU	Double-hollow-metal-door
Material	Cold roll steel & Galvanized steel	Certificate	Warnock Hersey, ITS
Warranty	12 Months unless specified otherwise	Origin	China

China Double hollow metal door:

- 1. 60min/90min/180mins fire proof with WH certificate
 - 2. Double leafs with fireproof glasses
 - 3. Panic bar, door closer,fireproof handle,stainless steel hignes
 - 4. Masonry frame:
- 16 Gauge(cold roll or A60 Galv)
- 3 Hours Warnock Hersey fire label

Hollow Metal Door & Frame

(Fire Rating up to 3 hours & Positive Pressure)
(MECHANICALLY INTERLOCK SEAM, LAP SEAM, STITCHED SEAM AVAILABLE)

Best Option For Commercial / Institutional / Industrial Entrances

Extensively tested in fire, smoke, airlocks, burglar and other conditions

Door Specs.

Standard Core

- Insulating, fire-rated core
- Available in 1 1/2" or 2" thickness
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available

Special Options

- Insulating, fire-rated core
- Available in 1 1/2" or 2" thickness
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available

Prismatic Core

- Insulating, fire-rated core
- Available in 1 1/2" or 2" thickness
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available

Special Options

- Insulating, fire-rated core
- Available in 1 1/2" or 2" thickness
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available

Special Core

- Insulating, fire-rated core
- Available in 1 1/2" or 2" thickness
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available

Special Options

- Insulating, fire-rated core
- Available in 1 1/2" or 2" thickness
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available
- 1 1/2" core is standard
- 2" core is available

Hollow Metal Door & Frame

(Fire Rating up to 3 hours & Positive Pressure)

Frame Specs.

DRY WALL FRAMES

- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick

MASONRY FRAMES

- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick

DOUBLE-EGRESS

- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick
- 1 1/2" Thick

Wood Stud Anchor

Steel Stud Anchor

Wire Mesh

All fire products information on your reference only, subject to our standard products.

(以中文說明書為準，其餘為準)

SpeciDIRECT powered by 



LISTING REPORT - MANUFACTURING
Issued: Jul 17 2006 5:38PM

Inspection Tests And Evaluation Of

Mexin Series 1200, 1600, 1800 3-Hour Polystyrene Core Steel Fire Door (13901)

RENDERED TO
Chongqing Mexin Messon Doors Industry Co., Ltd.
No. 51 Baihe Road
Chongqing,
CHINA

GENERAL: This Report gives the results of the inspection, tests and evaluation of the above for compliance with applicable requirements of the following standards: ASTM E-152-81a UL 10(c) (1998) UBC 7-2 (1997) UBC 7-2 (1994) UL 10(b) (1997) ASTM E2074 (2000) NFPA 252 (2003) CAN / ULC S104 1980 R1985

This report is for the exclusive use of Intertek's Client and is provided pursuant to the agreement between Intertek and its Client. Intertek's responsibility and liability are limited to the terms and conditions of the agreement. Intertek assumes no liability to any party, other than to the Client in accordance with the agreement, for any loss, expense or damage occasioned by the use of this report. Only the Client is authorized to permit copying or distribution of this report and then only in its entirety. Any use of the Intertek name or one of its marks for the sale or advertisement of the tested material, product or service must first be approved in writing by Intertek. The observations and test results in this report are relevant only to the sample tested. This report by itself does not imply that the material, product, or service is or has ever been under an Intertek certification program. To verify a listing, call 888-347-6476, or check our searchable online Directory of Listed Products at www.intertek.com.



