

DREDGE PIPELINE

Dredge Hydraulic Gate Valve

Pressure: upto 2.5MPA Size: DN200 to DN1200 Hydraulic Cylinder and Rubber Sealing
Stainless Steel Wedge Gate and Heat Affected Valve Body Technical Specification ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Dredge Pipeline
Material	DN200 to DN1200 Hydraulic Cylinder and Rubber Sealing Stainless Steel We...
Weight / Size	upto 2.5MPA Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.	

Technical Specifications			
Category	Dredge Pipeline	Model / SKU	Dredge-Hydraulic-Gate-Valve
Material	DN200 to DN1200 Hydraulic Cylinder and Rubber Sealing Stainless Steel Wedge Gate and Heat Affected Valve Body Technical Specification DN(mm) D1(mm) A(mm) B(mm) h(mm) H(mm) L(mm) Weight(kg) 200 250 315 163 185 570 500 70 250 295 315 163 196 570 500 75 300 375 473 245 278 855 750 236 350 435 550 285 325 995 875 375 400 496 628 325 370 1135 998 555 450 558 706 365 416 1270 1122 624 500 614 776 402 458 1400 1234 830 550 675 854 442 504 1540 1358 1104 600 735 930 482 550 1680 1480 1430 650 794 1004 520 594 1820 1598 1800 700 856 1084 560 640 1960 1725 2260 750 916 1160 600 685 2100 1845 2768 800 976 1236 640 730 2240 1966 3296	Weight / Size	upto 2.5MPA Size:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS	China Dredge Hydraulic Gate Valve: Technical Specification
----------	--

China Dredge Hydraulic Gate Valve:

Pressure: upto 2.5MPA

Size: DN200 to DN1200

Hydraulic Cylinder and Rubber Sealing

Stainless Steel Wedge Gate and Heat Affected Valve Body

Technical Specification

DN(mm)	D1(mm)	A(mm)	B(mm)	h(mm)	H(mm)	L(mm)	Weight(kg)
200	250	315	163	185	570	500	70
250	295	315	163	196	570	500	75

300	375	473	245	278	855	750	236
350	435	550	285	325	995	875	375
400	496	628	325	370	1135	998	555
450	558	706	365	416	1270	1122	624
500	614	776	402	458	1400	1234	830
550	675	854	442	504	1540	1358	1104
600	735	930	482	550	1680	1480	1430
650	794	1004	520	594	1820	1598	1800
700	856	1084	560	640	1960	1725	2260
750	916	1160	600	685	2100	1845	2768
800	976	1236	640	730	2240	1966	3296