

ABRASIVE MATERIAL RUBBER HOSE

Dry Cement Hose

Used casting, steel, stone, sand, cement and other abrasive amterial in sandblacking service
Characteristics: high tensile; wear, weather, ozone and aging resistance Working
temperature: -20 TO 80...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Abrasive Material Rubber Hose
Standard	EN
Material	Used casting, steel, stone, sand, cement and other abrasive amterial in ...
Weight / Size	1:3 Main Specification ID OD Length Bend radium WP Weight in mm in mm ft...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Abrasive Material Rubber Hose	Model / SKU	Dry-Cement-Hose
Standard	EN	Material	Used casting, steel, stone, sand, cement and other abrasive amterial in sandblacking service Characteristics:
Weight / Size	1:3 Main Specification ID OD Length Bend radium WP Weight in mm in mm ft m in mm Psi Kg/cm² Kg/m 1 25.4 1.701 43.2 200 60 6 150 200 15 1.38 1 1/4 31.8 1.953 49.6 200 60 8 200 200 15 1.6 1 1/2 38.1 2.232 56.7 200 60 10 250 200 15 1.91 2 50.8 2.772 70.4 200 60 12 300 150 10 2.6 2 1/2 63.5 3.272 83.1 200 60 15 375 150 10 3.1 3 76.2 3.811 96.8 200 60 20 500 150 10 3.95 4 101.6 5.047 128.2 200 60 28 700 150 10 6.48 5 127 6.091 154.7 100 30 40 1000 150 10 8.48 6 152.4 7.177 182.3 100 30 48 1200 150 10 11.07 8 203.2 9.268 235.4 100 30 64 1600 150 10 16.28 10 254 11.63 295.4 100 30 100 2500 100 7 26.05 12 304.8 13.866 352.2 100 30 120 3000 100 7 35.98	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	China Dry Cement Hose: Main Specification
----------	---

- China Dry Cement Hose:
- Used casting, steel, stone, sand, cement and other abrasive amterial in sandblacking service
 - Characteristics: high tensile; wear, weather, ozone and aging resistance
 - Working temperature: -20 TO 80°C
 - Safety Factor: 1:3

Main Specification

ID		OD		Length		Bend radium		WP		Weight
in	mm	in	mm	ft	m	in	mm	Psi	Kg/cm²	Kg/m
1	25.4	1.701	43.2	200	60	6	150	200	15	1.38

1 1/4	31.8	1.953	49.6	200	60	8	200	200	15	1.6
1 1/2	38.1	2.232	56.7	200	60	10	250	200	15	1.91
2	50.8	2.772	70.4	200	60	12	300	150	10	2.6
2 1/2	63.5	3.272	83.1	200	60	15	375	150	10	3.1
3	76.2	3.811	96.8	200	60	20	500	150	10	3.95
4	101.6	5.047	128.2	200	60	28	700	150	10	6.48
5	127	6.091	154.7	100	30	40	1000	150	10	8.48
6	152.4	7.177	182.3	100	30	48	1200	150	10	11.07
8	203.2	9.268	235.4	100	30	64	1600	150	10	16.28
10	254	11.63	295.4	100	30	100	2500	100	7	26.05
12	304.8	13.866	352.2	100	30	120	3000	100	7	35.98