

MARINE LIGHTING FIXTURES

DZ-L1 Solar Navigation Light

Model: DZ-L1/DZ-L1S Visible range:0-3km(About 2 NM) Rated power:1.5W Battery capacity (lithium cell):3600mAh Working voltage:3.7V Charging current:150mA Discharging current:320mA Protection grade:IP65 Working te...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Lighting Fixtures
Standard	EN
Material	DZ-L1/DZ-L1S Visible range:0-3km(About 2 NM) Rated power:1.5W Battery ca...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Lighting Fixtures	Model / SKU	DZ-L1-Solar-Navigation-Light
Standard	EN	Material	DZ-L1/DZ-L1S Visible range:0-3km(About 2 NM) Rated power:1.5W Battery capacity (lithium cell):3600mAh Working voltage:3.7V Charging current:150mA Discharging current:320mA Protection grade:IP65 Working temperature:-10°C~55°C Housing material:PC Solar panel material:Polysilicon Light source:
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

China DZ-L1 Solar Navigation Light:

Model: DZ-L1/DZ-L1S

Visible range:0-3km(About 2 NM)

Rated power:1.5W

Battery capacity (lithium cell):3600mAh

Working voltage:3.7V

Charging current:150mA

Discharging current:320mA

Protection grade:IP65

Working temperature:-10°C~55°C

Housing material:PC

Solar panel material:Polysilicon

Light source: 18*chip LED

Light color: red/white/green/yellow(other color can be customized)

Flash frequency changes with the working voltage, if working voltage higher, it flashes faster, and vice versa

Application : ocean、 river、 road,engineering,etc

