

MARINE WINDLASS

Electric Double Chain Drum Windlass

Electric Double Chain Drum Windlass: Speed:9~20m/min Anchor Chain Diameter: 12.5~114mm Driven Mode: Electric Motor (380V/440V/220V) Chain Diameter(mm) Ra...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Windlass
Standard	DIN
Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Electric-Double-Chain-Drum-Windlass
Standard	DIN	Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS	Warranty	12 Months unless specified otherwise
Origin	China		

Electric Double Chain Drum Windlass:

Speed:9~20m/min

Anchor Chain Diameter: 12.5~114mm

Driven Mode: Electric Motor (380V/440V/220V)

Chain Diameter(mm)	Rated Load(KN AM2)	Overload (KN AM2)	Holding Load(KN AM2)	Power (KW)
12.5	6.6	9.9	41.4	2.4/1.5
14	8.3	12.5	52.2	3.3/2.2

16	10.9	16.4	67.5	3.3/2.2
17.5	13	19.5	80.5	4.3/1.7
19	15.3	23	94.9	6/2.5
20.5	17.9	26.9	109.8	6/2.5
22	20.6	30.9	126	6/2.5
24	24.5	36.8	145	8.5/3.5
26	28.7	43	175	8.5/3.5
28	33.3	49.9	202	11/11/7.5
30	38.3	57.5	231	11/11/7.5
32	43.5	65.3	262	12/3.5
34	49.1	73.6	295	16/16/11
36	55.1	82.6	329	18/5
38	61.3	91.9	365	22/22/16
40	68	102	403	22/22/16
42	74.5	111.7	442	22/22/16
44	82.3	123.5	486	30/30/22
46	89.9	134.9	527	30/30/22