

MARINE WINDLASS

Electric Single Gypsy Windlass with Closed Gear Box

ISO9001 Supplier

Class Certificate

Export Supply

Electric Single Gypsy Windlass: Speed:9~20m/min Anchor Chain Diameter: 12.5~114mm
Driven Mode: Electric Motor (380V/440V/220V) The closed gear box can avoid the pollution of the ship from the gear...



Key Highlights

Category	Marine Windlass
Standard	DIN
Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Windlass	Model / SKU	Electric-Single-Gypsy-Windlass-with-Closed-Gear-Box
Standard	DIN	Material	Cast Steel
Certificate	CCS, BV, ABS, DNV/GL, LR, NK, IRS, RMRS	Warranty	12 Months unless specified otherwise
Origin	China		

Electric Single Gypsy Windlass:

Speed:9~20m/min

Anchor Chain Diameter: 12.5~114mm

Driven Mode: Electric Motor (380V/440V/220V)

The closed gear box can avoid the pollution of the ship from the gear box lubrication oil, improve the lubrication effect of gear transmission, reduce the lubrication oil use amount.

Chain Diameter(mm)	Rated Load(KN AM2)	Overload (KN AM2)	Holding Load(KN AM2)	Power (KW)
12.5	6.6	9.9	41.4	2.4/1.5
14	8.3	12.5	52.2	3.3/2.2
16	10.9	16.4	67.5	3.3/2.2
17.5	13	19.5	80.5	4.3/1.7
19	15.3	23	94.9	6/2.5
20.5	17.9	26.9	109.8	6/2.5
22	20.6	30.9	126	6/2.5
24	24.5	36.8	145	8.5/3.5
26	28.7	43	175	8.5/3.5
28	33.3	49.9	202	11/11/7.5
30	38.3	57.5	231	11/11/7.5
32	43.5	65.3	262	12/3.5
34	49.1	73.6	295	16/16/11
36	55.1	82.6	329	18/5
38	61.3	91.9	365	22/22/16
40	68	102	403	22/22/16
42	74.5	111.7	442	22/22/16
44	82.3	123.5	486	30/30/22
46	89.9	134.9	527	30/30/22