

MARINE WINCH

Electric Winch

Electric Winch Main Specification We can design the marine electric, hydraulic, diesel winches with specification from 10KN to 3000kN), our winch comply with international shipbuilding requirements and they h...

ISO9001 Supplier

Class Certificate

Export Supply

Loading product image...

Key Highlights

Category	Marine Winch
Standard	DIN
Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Winch	Model / SKU	Electric-Winch
Standard	DIN	Material	Cast steel
Certificate	ABS,LR, BV, GL, CCS, RINA, IRS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Electric Winch
- Main Specification
- Main Parameter

Electric Winch

Main Specification

We can design the marine electric, hydraulic, diesel winches with specification from 10KN to 3000kN), our winch comply with international shipbuilding requirements and they have been approved and awarded certificates by different shipping classification societies, such as CCS, ABS, BV, GL, DNV, LR, KR, NK, RINA.

The electric winches are used in inland river boats and coastal ships for mooring hoisting.

Main Parameter

电动（液压）绞车				
Electric（Hydraulic）Winch				
额定拉力 Rated Pull (kN)	额定速度 Rated Speed (m/min)	卷筒容量 Drum Capacity (ϕ mm x m)	电动机功率 Motor Power (kW)	
			电动 Electric	液压 Hydraulic
5	≥ 12	$\phi 8 \times 100$	3/1.2	
10	≥ 12	$\phi 10 \times 150$	4.3/1.7	5.5
20	≥ 12	$\phi 15 \times 150$	8.5/3.5	11
30	≥ 15	$\phi 17 \times 150$	11/1/7.5	15
40	≥ 15	$\phi 18 \times 150$	16/16/11	22
50	≥ 15	$\phi 20.5 \times 180$	22/22/16	30
75	≥ 15	$\phi 26 \times 200$	30/30/22	45
80	≥ 15	$\phi 26 \times 200$	30/30/22	37
100	≥ 15	$\phi 30 \times 200$	45/45/30	45
150	≥ 15	$\phi 30 \times 200$	45/45/30	55
160	≥ 15	$\phi 32 \times 250$	60/60/45	75
200	≥ 9.6	$\phi 41 \times 250$	45/45/30	75
250	≥ 15	$\phi 44.5 \times 250$	60/60/45	90
315	≥ 7.8	$\phi 522 \times 250$	60/60/45	90
400	≥ 7.8	$\phi 56 \times 250$	85/85/64	110
450	≥ 6	$\phi 56 \times 250$	85/85/64	110
500	≥ 7.8	$\phi 58 \times 250$	85/85/64	110
550	≥ 6	$\phi 64 \times 250$	85/85/64	132
600	≥ 6	$\phi 64 \times 250$	85/85/64	132
650	≥ 6	$\phi 70 \times 250$	85/85/64	132
1000	≥ 4	$\phi 85 \times 250$	85/85/64	132
1200	≥ 4	$\phi 95 \times 250$	120/120/90	160
1500	≥ 4	$\phi 95 \times 250$	150/150/72	200
1800	≥ 4	$\phi 95 \times 250$	150/150/72	250
2000	≥ 4	$\phi 100 \times 250$	180/180/135	270
3000	≥ 3	$\phi 134 \times 250$	/	315
4000	≥ 3	$\phi 154 \times 250$	/	400
5000	≥ 2.5	$\phi 170 \times 250$	/	450
6000	≥ 2.2	$\phi 188 \times 250$	/	450

注：具体技术参数以技术规格书和图样为准。
Note: Specific technical parameters take technical specifications and drawings as standard.