

ELECTRIC OPERATED FIRE MONITOR

Electrical Water Fire Monitor 80L/S

TYPE: JBSX-EM-EE Flow Range: 80L/S Automatic Nozzle (1250GPM) Working Pressure: 10 bar~ 12 bar Max Reach @ Max Flow: 80m Max. Range of motion: +/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec ...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Electric Operated Fire Monitor
Standard	EN
Material	+/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Ma...
Weight / Size	12 inch (30.5CM) power supply : 12/24VDC or 100-230VAC Power Consumption n...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Electric Operated Fire Monitor	Model / SKU	Electrical-Water-Fire-Monitor-80L-S
Standard	EN	Material	+/-90°Vert , 350°Rot Max fog angle : 120° Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : bronze Material (nozzle) : Aluminum Extension:
Weight / Size	12 inch (30.5CM) power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Electrical Water Fire Monitor 80L/S:

TYPE: JBSX-EM-EE

Flow Range: 80L/S Automatic Nozzle (1250GPM)

Working Pressure: 10 bar~ 12 bar

Max Reach @ Max Flow: 80m

Max. Range of motion: +/-90°Vert , 350°Rot

Max fog angle : 120°

Turning speed : 18 degrees/sec

Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available

Material (Gear) : bronze

Material (nozzle) : Aluminum

Extension: 12 inch (30.5CM)

power supply : 12/24VDC or 100-230VAC

Power Consumption normal/Max : 50W/150W

Weight incl. nozzle : appox 28kg

Cable Length Monitor- CPU : 5m

Cable Length Joystick-CPU : 5m standard/ other length available

Pump requirement for minimum performance : 80L/S@ 8 bar

Pipe dimensions for installation: 3 Inch

Monitor Inlet : 3" male BSP or DN100 flange

Extend Gun Inlet: 3 inch BSP male

Water Way Size: 3 inch

Monitor Outlet : 2.5 inch (65mm)

PACKAGE: SS MONITOR, NOZZLE, CONTROL BOX, JOYSTICK, CABLES, ELECTRIC EXTENDER, WIRELESS CONTROL (OPTIONAL)