

FIRE MONITOR

Electrical Water Fire Monitor (Riot Control) 20L/S

ISO9001 Supplier

Class Certificate

Export Supply

Type : JBPSKD20-riot control Flow Range: 20L/S (320GPM), Working Pressure: 6 bar~ 16 bar Max Reach @ Max Flow: 65M Max. Range of motion: +/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L Stainl...



Key Highlights

Category	Fire Monitor
Standard	EN
Material	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L S...
Weight / Size	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L S...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Fire Monitor	Model / SKU	Electrical-Water-Fire-Monitor-Riot-Control-20L-S
Standard	EN	Material	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : Bronze Material (nozzle) : stainless steel power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.
Weight / Size	+/-90°Vert , 350°Rot Turning speed : 18 degrees/sec Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available Material (Gear) : Bronze Material (nozzle) : stainless steel power supply : 12/24VDC or 100-230VAC Power Consumption normal/Max : 50W/150W Weight incl.	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

China Electrical Water Fire Monitor (Riot Control) 20L/S:

Type : JBPSKD20-riot control
 Flow Range: 20L/S (320GPM),
 Working Pressure: 6 bar~ 16 bar
 Max Reach @ Max Flow: 65M
 Max. Range of motion: +/-90°Vert , 350°Rot
 Turning speed : 18 degrees/sec
 Material (body) : 304L Stainless Steel, 316L Stainless Steel is also available
 Material (Gear) : Bronze
 Material (nozzle) : stainless steel
 power supply : 12/24VDC or 100-230VAC
 Power Consumption normal/Max : 50W/150W
 Weight incl. nozzle : appox 20kg
 Cable Length Monitor- CPU : 5m
 Cable Length Joystick-CPU : 5m standard/ other length available
 Pump requirement for minimum performance : 20L/S@ 6 bar
 Pipe dimensions for installation: 2-2.5 Inch
 Monitor Inlet : 2.5" male BSP or DN65 flange
 Monitor Outlet : 2 inch (50mm)
 Water way size: 2 inch

PACKAGE: SS MONITOR, NOZZLE, CAMERAL, INFARED LAMP, CONTROL BOX, JOYSTICK, CABLES, WIRELESS CONTROL (OPTIONAL),

