

GAS FITTING

Emergency Cut-off Valve

We supply the Emergency Cut-off Valve with high quality, also customized service available and ship from stock.

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

|             |                                                                                |
|-------------|--------------------------------------------------------------------------------|
| Category    | Gas Fitting                                                                    |
| Standard    | EN                                                                             |
| Material    | Main Specification Material<br>Dust casting iron Operation medium Gasoline,... |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS                                     |

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

|             |                                            |             |                                                                                                                                                                                                                                                        |
|-------------|--------------------------------------------|-------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Category    | Gas Fitting                                | Model / SKU | Emergency-Cut-off-Valve                                                                                                                                                                                                                                |
| Standard    | EN                                         | Material    | Main Specification Material Dust casting iron Operation medium Gasoline,diesel oil,coal oil Nominal Pressure 0.2Mpa Operating environment -20°C ~ +55°C Threaded joint of the inlet and outlet BSPT1/2 Rated of valve closure 0.5S Flow range 120L/min |
| Certificate | ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS | Warranty    | 12 Months unless specified otherwise                                                                                                                                                                                                                   |
| Origin      | China                                      |             |                                                                                                                                                                                                                                                        |



## Main Specification

| Material                               | Dust casting iron | Operation medium       | Gasoline,diesel oil,coal oil |
|----------------------------------------|-------------------|------------------------|------------------------------|
| Nominal Pressure                       | 0.2Mpa            | Operating environment  | -20℃ ~ +55℃                  |
| Threaded joint of the inlet and outlet | BSPT1/2           | Rated of valve closure | 0.5S                         |
| Flow range                             | 120L/min          |                        |                              |