

MARINE FUEL HOMOGENIZER

Energy Saving Marine Fuel Homogenizer

Independent brand fuel homogenizer developed, with significant reduction in diesel oil, improving combustion and regeneration of waste oil and other effects, can well solve the diesel owners with high viscosity low qu...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Marine Fuel Homogenizer
Standard	DIN
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Marine Fuel Homogenizer	Model / SKU	Energy-Saving-Marine-Fuel-Homogenizer
Standard	DIN	Surface	High hardness of the tooth surface, to enhance the shear efficiency and reduce the shear tooth surface wear.
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- China Energy Saving Marine Fuel Homogenizer:
- Energy Saving Marine Fuel Homogenizer Technical Specifications
- Advantage

China Energy Saving Marine Fuel Homogenizer:

Independent brand fuel homogenizer developed, with significant reduction in diesel oil, improving combustion and regeneration of waste oil and other effects, can well solve the diesel owners with high viscosity low quality fuel produced increased, equipment wear and other issues.

We can provide marine fuel homogenizer installation design, installation guidance, maintenance work, for the owners in energy saving, environmental protection, reduce shipping costs and other aspects of strong support.

Advantage

1. Improve the fault alarm system to ensure safe use.
2. The use of international brand motor drive, to ensure the normal use of harsh conditions.
3. Classification society authority certification, reliable quality.
4. Good cost control, more favorable price and service.
5. Adopt the current popular mainstream design scheme, that is stator rotor structure, and further optimize the design in the product.
6. More precise stator / rotor machining, high speed and severe dynamic balancing test, ultra smooth running, little noise. High hardness of the tooth surface, to enhance the shear efficiency and reduce the shear tooth surface wear.
7. The internal use of sliding bearings, fuel self-lubricating, long life.
8. Apply magnetic coupling, completely avoid the risk of oil leakage, and automatically protect the motor overload.

Energy Saving Marine Fuel Homogenizer Technical Specifications

Type	FH03030	FH03055	FH10075	FH10110	FH20150	FH20220
Capacity,m3/h	1 ~ 3	3 ~ 5	5 ~ 10	10 ~ 15	15 ~ 20	> 20
Power,Kw	3.0	5.5	7.5	11.0	15.0	22.0
Voltage,V/Hz	400/50,440/60					
Pressure,Mpa	< 1.6					
Max.temp. °C	150					