

MARINE EXPLOSION-PROOF LIGHTS SERIES

Explosion-proof Fluorescent Light
CFY20 CFY30 CFY40

ISO9001 Supplier

Class Certificate

Export Supply

Used to cabin illumination in the hazardous area such as chemical factory, oil refinery, oil and gas plant with expolive gas environment.



Key Highlights

Category	Marine Explosion-proof Lights Series
Standard	EN
Material	Stainless Steel
Weight / Size	Type CFY20-2 CFY20-1 CFY30-2 CFY30-1 CFY40-2 CFY40-1 Explosion-proof Mar...
Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications			
Category	Marine Explosion-proof Lights Series	Model / SKU	Explosion-proof-Fluorescent-Light-CFY20-CFY30-CFY40
Standard	EN	Material	Stainless Steel
Weight / Size	Type CFY20-2 CFY20-1 CFY30-2 CFY30-1 CFY40-2 CFY40-1 Explosion-proof Mark Exd II C T6 Voltage 220V/50Hz, 220V/60Hz, 110V/60Hz Power 2x20W 1x20W 2x30W 1x30W 2x40W 1x40W Lamp Holder G13 Protection Class IP56 IP56 IP56 IP56 IP56 IP56 Cable Diameter Dia13-14mm Weight 11.5kg 11.5kg 13.5kg 13.5kg 15kg 15kg	Certificate	ABS, LR, BV, DNVGL, NK, KR, IRS, RMRS, CCS
Warranty	12 Months unless specified otherwise	Origin	China

CONTENTS	China Explosion-proof Fluorescent Light CFY20 CFY30 CFY40:	Main Specification:
----------	--	---

China Explosion-proof Fluorescent Light CFY20 CFY30 CFY40:



Used to cabin illumination in the hazardous area such as chemical factory, oil refinery, oil and gas plant with expolive gas environment.

Main Specification:

Type	CFY20-2	CFY20-1	CFY30-2	CFY30-1	CFY40-2	CFY40-1
Explosion-proof Mark	Exd II C T6					
Voltage	220V/50Hz, 220V/60Hz, 110V/60Hz					

Power	2x20W	1x20W	2x30W	1x30W	2x40W	1x40W
Lamp Holder	G13					
Protection Class	IP56	IP56	IP56	IP56	IP56	IP56
Cable Diameter	Dia13-14mm					
Weight	11.5kg	11.5kg	13.5kg	13.5kg	15kg	15kg