

CHAIN SLING

W01 Eye Type Flat Sling

Description: Flat hoisting belt is also called flat ring hoisting belt: flat hoisting belt is more economical and practical, soft texture, can constantly change the lifting point, there are many ways to use! The fl...

ISO9001 Supplier

Class Certificate

Export Supply



Key Highlights

Category	Chain Sling
Standard	DIN
Material	Cotton, nylon, synthetic fiber, polyester fiber
Weight / Size	Size can be determined according to customer requirements (1-50t load, 1...
Certificate	CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS

We can supply according to your requirement, drawings, class certificate needs, and delivery schedule.

Technical Specifications

Category	Chain Sling	Model / SKU	EYE-TYPE-TYPE-W01
Standard	DIN	Material	Cotton, nylon, synthetic fiber, polyester fiber
Weight / Size	Size can be determined according to customer requirements (1-50t load, 1-100m long) bearing surface width, can share the pressure of surface load;	Surface	Size can be determined according to customer requirements (1-50t load, 1-100m long) bearing surface width, can share the pressure of surface load;
Certificate	CNAS, API, CCS, DNV.GL, KR, BV, CE, PCT.GOST, JIS, GS	Warranty	12 Months unless specified otherwise
Origin	China		

CONTENTS

- Description:
 - Technical requirement:
- Feature:
 - Data Sheet:

Description:

Flat hoisting belt is also called flat ring hoisting belt: flat hoisting belt is more economical and practical, soft texture, can constantly change the lifting point, there are many ways to use! The flat lifting belt can be divided into single layer, double deck and four layers, with various stitching methods. Size can be determined according to customer requirements (1-50t load, 1-100m long) bearing surface width, can share the pressure of surface load; flat hoisting belt hoisting surface smooth and fine objects will not damage the lifted object, can be added anti-wear protective sleeve and anti-cutting protective sleeve, safety factor ratio is 6:1 and 7:1.

The rated load is distinguished according to the international standard color, even if the hoisting belt is rubbed and damaged, it is easy to identify.

Feature:

Industrial yarns are woven and dyed into industrial ribbons of 15mm, 30mm, 50mm, 60mm, 75mm, 90mm, 100mm, 120mm, 150mm, 180mm, 240mm, 300mm, lug width 30mm, 50mm, 60mm, 70mm, 80mm, 100mm. Industrial tapes are used for industrial sewing to form flat lifting belts. There is a hanging ring on both sides of the flat ring eye lifting belt, with an anti-wear sheath on the rings. The flat ring eye lifting is stitched together with several layers of ribbon in the middle. The flat ring hoisting belt is just a circle.

Technical requirement:

- (1) light weight, good flexibility, easy to bend, easy to use;
- (2) do not damage the appearance of hanging objects, and maintain strong.
- (3) safe lifting and high safety factor.
- (4) high tensile strength, beautiful color and easy to distinguish.
- (5) it is an insulator.
- (6) lifting belt has long life, good corrosion resistance and wear resistance.
- (7) progress, rest and obedience, and save capital;
- (8) It is widely used in aviation, astronautics, nuclear power establishment, military manufacturing, port handling, electric power equipment, machine processing, chemical steel, shipbuilding, transportation and other fields.

Data Sheet:



Art.No.	Working Load Limit (kg)	Approx Width (mm)		Minimum Length L (m)	Eye Length (mm)
		5、 6:1	7:01		
W01-01	1000	25	30	1.1	350
W01-02	2000	50	60	1.2	400
W01-03	3000	75	90	1.3	450

W01-04	4000	100	120	1.4	500
W01-05	5000	125	150	2	550
W01-06	6000	150	180	2	600
W01-08	8000	200	240	2	700
W01-10	10000	250	300	3	800
W01-12	12000	300	300	3	900